

INDUSTRIAL COMPONENT DATA

CLP4MA2A115 CARLO GAVAZZI Selected parameters SYSTEM System HOUSING Rectangular SENSING FUNCTION Filling and..

Brand: CARLO GAVAZZI | Manufacturer Part Number: CLP4MA2A115



Manufacturer	CARLO GAVAZZI
MPN / Reference	CLP4MA2A115
Catalog number	10000
Category	(Fill) level monitoring relay
Minimum order	1 Pcs
Document ID	EO-9713534B7B
Generated	2026-08-01

Product Overview

Selected parameters SYSTEM System HOUSING Rectangular SENSING FUNCTION Filling and Emptying CONNECTION Plug and socket OUTPUT Relay DPDT MATERIAL Plastic Others HOUSING 35,5 x 81 x 63 mm SENSING FUNCTION 250 ohm to 500 kohm MATERIAL NORYL ADDITIONAL Alarm HiHi and LoLo

2 to 4 point conductive level controller with potentiometer, Power supply 115 VAC

Conductive 2 to 4-point level controller, plug in mount, filling-emptying with multifunctions, sensitivity 250 ohm -500 Kohm, 2 x SPST relay output, supply voltage 115VAC, 35.5x81x60,2mm housing, IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	CARLO GAVAZZI > Sensors > Conductive Level
--------------	--

Additional Product Information

Specifications

Number of input probes5Adjustable sensitivityNoNumber of relay outputs1Min on-delay time1 sMax on-delay time1 sMin off-delay time1 sMax off-delay time1 sRated operating voltage0 V ... 0 VConnection typePlug-in connectionProduct width35.5 mm

ETIM for CLP4MA2A115 Relays (EC001447)

Feature Name

Feature Value

Type of electric connection (EF003961)

Plug-in connection

With detachable clamps (EF003340)

No

Number of inputs for electrodes (EF003427)

5

Min. adjustable operate delay time (EF008195)

1 s

Max. permitted operate delay time (EF008194)

1 s

Min. adjustable off-delay time (EF008192)

1 s

Max. permitted off-delay time (EF008191)

1 s

Response value sensitivity adjustable (EF003429)

No

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as normally open contact (EF008256)

1

Number of contacts as change-over contact (EF008257)

1

Physical measurement principle (EF008238)

Conductive

Cascadable (EF000507)

No

Width (EF000008)

35.5 mm

Height (EF000040)

81 mm

Depth (EF000049)

60.2 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / CLP4MA2A115 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.