

INDUSTRIAL COMPONENT DATA

PD180CBT30MU CARLO GAVAZZI Selected parameters SYSTEM Through-beam HOUSING rectangular SENSING RANGE 30

Brand: CARLO GAVAZZI | Manufacturer Part Number: PD180CBT30MU



Manufacturer	CARLO GAVAZZI
MPN / Reference	PD180CBT30MU
Catalog number	10000
Category	Through beam photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-6C14917550
Generated	2026-07-29

Product Overview

Selected parameters SYSTEM Through-beam HOUSING rectangular SENSING RANGE 30 ... 50 m CONNECTION
Terminals OUTPUT Battery Supply MATERIAL Plastic Others SENSING RANGE 30 m HOUSING 180 x 51 x 49 mm
MATERIAL PC ADDITIONAL Test input

Photocell barrier for industrial doors and accesses, Emitter

Photoelectric Through-beam Emitter, Range: 30000mm, Infrared light 850nm, Power Supply Battery, Screw Terminals,
51x49x180mm housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Photoelectric

Additional Product Information

Specifications

Rated operating distance30000 mmOutput typeOtherOutput functionOtherConnection typeScrew connectionHousing
typeRectangularHousing MaterialPlasticType of lightInfrared lightSensing modeLight-/dark switchingDegree of
protectionIP55Rated Operational voltage UB at DC3.6 V ... 3.6 V

ETIM for PD180CBT30MU Sensors (EC002716)

Feature Name

Feature Value

Scope of delivery of the one-way system (EF004032)

Transmitter

Max. opening angle (EF002642)

4.1 °

Pre failure notice (EF004129)

No

With time function (EF003582)

No

Rated switching distance (EF008289)

30000 mm

Max. switching distance (EF007367)

30000 mm

Max. output current (EF001315)

1000 mA

With reflector (EF007448)

No

Analogue output 0 V ... 10 V (EF006807)

No

Analogue output 0 mA ... 20 mA (EF006808)

No

Analogue output 4 mA ... 20 mA (EF006810)

No

Analogue output -10 V ... +10 V (EF006809)

No

With other analogue output (EF007485)

No

Setting procedure (EF003994)

Manual adjustment

With communication interface analogue (EF007305)

No

With communication interface AS-Interface (EF007306)

No

With communication interface CANOpen (EF007307)

No

With communication interface DeviceNet (EF007308)

No

With communication interface Ethernet (EF007309)

No

With communication interface INTERBUS (EF007310)

No

With communication interface PROFIBUS (EF007311)

No

With communication interface RS-232 (EF007312)

No

With communication interface RS-422 (EF007313)

No

With communication interface RS-485 (EF007314)

No

With communication interface S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PD180CBT30MU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.