

INDUSTRIAL COMPONENT DATA

PD30CNT15PPDU CARLO GAVAZZI Selected parameters SYSTEM Through-beam HOUSING rectangular SENSING RANGE 6

Brand: CARLO GAVAZZI | Manufacturer Part Number: PD30CNT15PPDU



Manufacturer	CARLO GAVAZZI
MPN / Reference	PD30CNT15PPDU
Catalog number	10000
Category	Through beam photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-E7B27CF3A0
Generated	2026-08-01

Product Overview

Selected parameters SYSTEM Through-beam HOUSING rectangular SENSING RANGE 6 ... 20 m CONNECTION Cable
OUTPUT DC PNP MATERIAL Plastic Others SENSING RANGE 15 m HOUSING 30 x 20 x 10,8 mm MATERIAL ABS
ADDITIONAL Dust output

Amplific barrier photocell. Built-in, Miniature, VCC plastic, Teach-in adjustment, Dirt alarm

Photoelectric Through-beam Receiver, Range: 15000mm, Infrared light 880nm, Power Supply 10-30VDC, Dust Output,
PNP Output, N.O. or N.C., light or dark switching, Cable connection, 10x30x20mm housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Sensors > Photoelectric

Additional Product Information

Specifications

Rated operating distance15000 mmOutput typePNPOutput functionProgrammable/configurableConnection
typeCableHousing typeRectangularHousing MaterialPlasticType of lightInfrared lightSensing modeLight-/dark
switchingDegree of protectionIP67Rated Operational voltage UB at DC10 V ... 30 V

ETIM for PD30CNT15PPDU Sensors (EC002716)

Feature Name

Feature Value

Scope of delivery of the one-way system (EF004032)

Receiver

Max. opening angle (EF002642)

2 °

Pre failure notice (EF004129)

No

With time function (EF003582)

No

Rated switching distance (EF008289)

15000 mm

Max. switching distance (EF007367)

15000 mm

Max. output current (EF001315)

100 mA

With reflector (EF007448)

No

Analogue output 0 V ... 10 V (EF006807)

No

Analogue output 0 mA ... 20 mA (EF006808)

No

Analogue output 4 mA ... 20 mA (EF006810)

No

Analogue output -10 V ... +10 V (EF006809)

No

With other analogue output (EF007485)

No

Setting procedure (EF003994)

Teach-In

With communication interface analogue (EF007305)

No

With communication interface AS-Interface (EF007306)

No

With communication interface CANOpen (EF007307)

No

With communication interface DeviceNet (EF007308)

No

With communication interface Ethernet (EF007309)

No

With communication interface INTERBUS (EF007310)

No

With communication interface PROFIBUS (EF007311)

No

With communication interface RS-232 (EF007312)

No

With communication interface RS-422 (EF007313)

No

With communication interface RS-485 (EF007314)

No

With communication interface SSD (EF007...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / PD30CNT15PPDU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.