

INDUSTRIAL COMPONENT DATA

B5X-PIR90-U CARLO GAVAZZI Selected parameters TYPE Sensors / Detector HOUSING 55 x 55 POWER SUPPLY Bus-power..

Brand: CARLO GAVAZZI | Manufacturer Part Number: B5X-PIR90-U



Manufacturer	CARLO GAVAZZI
MPN / Reference	B5X-PIR90-U
Catalog number	10000
Category	Movement sensor for bus system
Minimum order	1 Pcs
Document ID	EO-73AC13DC02
Generated	2026-08-06

Product Overview

Selected parameters TYPE Sensors / Detector HOUSING 55 x 55 POWER SUPPLY Bus-powered Others TYPE PIR detector HOUSING PIR sensor to be mounted in Elko, Jung and Gira frames POWER SUPPLY Bus-powered MAIN CHARACTERISTICS 90° PIR detector, 10 m detection range
Passive presence/motion infrared detector for Smart Dupline®
90 Degrees Angle for Presence and Movement Detection, 55X55

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **CARLO GAVAZZI > Controls > Energy Management, Software and Accessories**

Additional Product Information

Specifications

Mounting method Flush mounted (plaster) With approval according to UL Yes
ETIM for B5X-PIR90-U Installation bus systems (EC001582)

Feature Name
Feature Value

Bus system KNX (EF001499)

No

Bus system KNX-RF (Radio Frequency) (EF008855)

No

Bus system radio frequency (EF001500)

No

Bus system LON (EF003831)

No

Bus system Powernet (EF001501)

No

Other bus systems (EF003811)

Dupline

Radio frequency bidirectional (EF009466)

No

Model (EF000010)

Movement sensor

Mounting method (EF000003)

Flush mounted

Material (EF002169)

Plastic

Material quality (EF001257)

Thermoplastic

Surface protection (EF000139)

Decor

Surface finishing (EF006569)

Matt

Colour (EF000007)

Black

Transparent (EF006243)

No

With bus connection (EF001504)

Yes

Substation input (EF003876)

No

Creep-under protection (EF000147)

No

Operation mode switch (EF004530)

No

Animal zone (EF006311)

Yes

Staircase light controller (EF001098)

Yes

Response value luminosity adjustable (EF007575)

Yes

Teach-function for response value luminosity (EF003898)

Yes

Switch-off delay self-learning (EF007667)

No

Optimum mounting height (EF008011)

1.1 m

Max. reach sideways (EF001323)

5 m

Max. reach frontally (EF001322)

10 m

Diameter reach on floor (EF003843)

4 m

Detection angle vertical (EF006581)

0 °

Detection angle horizontal (EF006582)

0 °

Number of channels (EF000259)

1

Min. switch-on time (EF006589)

1 s

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / B5X-PIR90-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.