

INDUSTRIAL COMPONENT DATA

SPDM24751 CARLO GAVAZZI Model: AC to DC switching power supply, Ac input voltage: 85VAC-264VAC, Output power..

Brand: CARLO GAVAZZI | Manufacturer Part Number: SPDM24751



Manufacturer	CARLO GAVAZZI
MPN / Reference	SPDM24751
Catalog number	24751
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-FCA7DAB7A2
Generated	2026-08-05

Product Overview

Model: AC to DC switching power supply, Ac input voltage: 85VAC-264VAC, Output power: 72W, Parallel connection: no, Input type: Single phase or DC, Output voltage: 24Vdc, Pfc: no, Dc input voltage: 120 - 370V, Terminal type: Screw terminal, Output rdy: no

Single-phase power supply, output 24 Vdc, output current 3 A, output power 72 W

Switching Power Supply, Medium Compact, AC/DC, 75W, 24V, Screw Terminals, IP20, DIN-Rail Mounting, Over-load, Over-voltage and Short-circuit Protections, 22.5x90x100mm plastic housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path CARLO GAVAZZI > Switches > Power supplies

Additional Product Information

Specifications

Rated output voltage DC24 VPower output75 WMax. output current DC3 ATerminal typeScrew connectionRail mounting possibleYesWall mounting possibleNoDegree of protection (IP)IP20Width40.5 mmHeight90 mmDepth100 mm
ETIM for SPDM24751 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

23.76 V

2nd secondary output voltage (EF006797)

0 V

3rd secondary output voltage (EF006800)

0 V

Max. output current 1 (EF008284)

3 A

Max. output current 2 (EF008285)

0 A

Max. output current 3 (EF008286)

0 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

24 V

Nominal value output voltage 2 (EF009394)

0 V

Nominal value output voltage 3 (EF009395)

0 V

Nominal value output current 1 (EF009396)

3 A

Nominal value output current 2 (EF009397)

0 A

Nominal value output current 3 (EF009398)

0 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

100 V

Rated supply voltage AC 60 Hz (EF007077)

100 V

Rated supply voltage DC (EF007078)

120 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

0.5 VA

Power output (EF003034)

75 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Screw connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No
Modular version (EF001126)
No
Width in number of modular spacings (EF002950)
0
Built-in width (EF000846)
40.5 mm
Built...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / SPDM24751 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.