

## INDUSTRIAL COMPONENT DATA

# UA18CSD08PPM1TI CARLO GAVAZZI System: Sensor, Housing: M18, Sensing range: 0,2 to 1 m, Connection: M12 plug ..

Brand: CARLO GAVAZZI | Manufacturer Part Number: UA18CSD08PPM1TI



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | CARLO GAVAZZI               |
| MPN / Reference | UA18CSD08PPM1TI             |
| Catalog number  | 10000                       |
| Category        | Ultrasonic proximity switch |
| Minimum order   | 1 Pcs                       |
| Document ID     | EO-E12C113492               |
| Generated       | 2026-08-04                  |

## Product Overview

System: Sensor, Housing: M18, Sensing range: >0,2 to 1 m, Connection: M12 plug DC, Output: DC PNP, Material: Plastic, Housing: M18 x 46,4 mm, Sensing range: 0,8 m, Material: Thermoplastic polyester  
Ultrasound with direct detection, PNP digital output, Sensing distance 80 to 800 mm.  
Ultrasonic sensor, Diffuse reflective, M18 plastic, M12 plug, Sn 80-800mm, PNP Output, Supply voltage 10-30Vdc, Current output 100mA, Operating temperature -20C - +60C, Switching frequency 5Hz, IP67, Teach-in

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                            |
|--------------|--------------------------------------------|
| Catalog path | CARLO GAVAZZI > Sensors > Conductive Level |
|--------------|--------------------------------------------|

## Additional Product Information

## Specifications

Rated operating distance80 mm ... 800 mmBlind zone80 mmDiameter18 mmAnalogue outputOtherOutput typePNPOutput functionConfigurableConnection typeM12 connectorHousing materialPlasticRated power supply10 V ... 30 VDegree of protectionIP67

ETIM for UA18CSD08PPM1TI Sensors (EC001849)

Feature Name

Feature Value

Type of analogy output (EF003958)

Other

Type of electric connection (EF003961)

Connector M12

Type of switching output (EF003962)

PNP

Type of switch function (EF003963)

Programmable/configurable

Blind zone (EF003986)

80 mm

Length of sensor (EF007334)

60.4 mm

Diameter sensor (EF007111)

18 mm

Adjustable distance (EF008209)

80 mm

Setting procedure (EF003994)

Teach-In

Measuring range length (EF008213)

80 mm

Construction type housing (EF004008)

Cylinder, screw-thread

Standard for interfaces (EF004017)

Other

No-load current (EF004028)

35 mA

Relative linearity deflection (EF004034)

1 %

Max. output current (EF001315)

100 mA

Ambient temperature (EF002386)

-20 °C

Supply voltage (EF004127)

10 V

Relative repeat accuracy (EF004100)

1 %

Switching frequency (EF003587)

5 Hz

Voltage type (EF000187)

DC

Synchronisation possible (EF004117)

No

Material active area of sensor (EF004133)

Glass

Housing material (EF001596)

Plastic

Material of cable sheath (EF004136)

Other

AWG-number (EF007010)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send CARLO GAVAZZI / UA18CSD08PPM1TI with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.