

INDUSTRIAL COMPONENT DATA

131B1312**FC-301P1K5T4E20H1XGXXXXSXXXXA4BXCXXXXDX****DANFOSS DRIVES****FC-301P1K5T4E20H1XGXXXXSXXXXA4BXCXXXXDX**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 1212519



Manufacturer	DANFOSS DRIVES
MPN / Reference	1212519
Catalog number	1212519
Category	VLT AUTOMATIONDRIVE FC 302
Minimum order	1 unit
Document ID	EO-5443B77603
Generated	2026-08-06

Product Overview

131B1312 FC-301P1K5T4E20H1XGXXXXSXXXXA4BXCXXXXDX DANFOSS DRIVES
FC-301P1K5T4E20H1XGXXXXSXXXXA4BXCXXXXDX

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS DRIVES > VLT AUTOMATIONDRIVE FC 302 - DANFOSS DRIVES

Additional Product Information

Frequency converter
FC-301P1K5T4E20H1XGXXXXSXXXXA4BXCXXXXDX
VLT® AutomationDrive FC-301
(P1K5) 1.5 KW / 2.0 HP,
Three phase, 380 - 480 VAC, (E20) IP20 / Chassis
(H1) RFI Class A1/B (C1)
No brake chopper
Graphical Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
Frame: A2

DeviceNet MCA 104, No B Option
No C1 option, No D option
Other options according to Model code
Product details
Gross weight 5.276 Kilogram
Net weight 4.43 Kilogram
Volume 21.569 Liter
EAN 5710107153732
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® AutomationDrive FC-
Series 301 301
Power Rating P1K5 (P1K5) 1.5 KW / 2.0 HP
Phase T Three phase
Mains Voltage 4 380 - 480 VAC
Enclosure E20 (E20) IP20 / Chassis
RFI Filter H1 (H1) RFI Class A1/B (C1)
Brake - Safe Stop X No brake chopper
LCP G Graphical Loc. Cont. Panel
Coating PCB X Not coated PCB
Mains Option X No Mains Option
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option A4 DeviceNet MCA 104
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size A2 A2
Typecode Part 1 FC-301P1K5T4E20H1XGX
Typecode Part 2 XXXSXXXXA4BXCXXXXDX
Product Catalog NO_VIEW NO VIEW
Power 160% (HO) [KW] 1.5 1.5
Height [mm] 268,0 268,0
Width w/ no C options [mm] 90,0 90,0
Width w/ two C options [mm] 150,0 150,0
Depth [mm] 205,0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 1212519 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.