

INDUSTRIAL COMPONENT DATA

131B2668**FC-301P1K1T4Z20H2XXXXXXXXSXXXXAXBXCXXXXDX****DANFOSS DRIVES****FC-301P1K1T4Z20H2XXXXXXXXSXXXXAXBXCXXXXDX**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 1212519



Manufacturer	DANFOSS DRIVES
MPN / Reference	1212519
Catalog number	1212519
Category	VLT AUTOMATIONDRIVE FC 302
Minimum order	1 unit
Document ID	EO-B1625A77A9
Generated	2026-08-06

Product Overview

131B2668 FC-301P1K1T4Z20H2XXXXXXXXSXXXXAXBXCXXXXDX DANFOSS DRIVES
FC-301P1K1T4Z20H2XXXXXXXXSXXXXAXBXCXXXXDX

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS DRIVES > VLT AUTOMATIONDRIVE FC 302 - DANFOSS DRIVES

Additional Product Information

Frequency converter
FC-301P1K1T4Z20H2XXXXXXXXSXXXXAXBXCXXXXDX
VLT® AutomationDrive FC-301
(P1K1) 1.1 KW / 1.5 HP,
Three phase, 380 - 480 VAC, IP20 / Chassis A1 Frame
RFI Filter
No brake chopper
No Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
Frame: A1

No A Option, No B Option
No C1 option, No D option
Other options according to Model code
Product details
Gross weight 3.366 Kilogram
Net weight 2.47 Kilogram
Volume 21.569 Liter
EAN 5702427219779
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® AutomationDrive FC-
Series 301 301
Power Rating P1K1 (P1K1) 1.1 KW / 1.5 HP
Phase T Three phase
Mains Voltage 4 380 - 480 VAC
Enclosure Z20 IP20 / Chassis A1 Frame
RFI Filter H2 RFI Filter
Brake - Safe Stop X No brake chopper
LCP X No Loc. Cont. Panel
Coating PCB X Not coated PCB
Mains Option X No Mains Option
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AX No A Option
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size A1 A1
Typecode Part 1 FC-301P1K1T4Z20H2XXX
Typecode Part 2 XXXSXXXAXBXCXXXDX
Product Catalog NO_VIEW NO VIEW
Power 160% (HO) [KW] 1.1 1.1
Height [mm] 200,0 200,0
Width w/ no C options [mm] 75,0 75,0
Depth [mm] 207,0 207,0
Depth with Option A/B [mm] 222,0 222,0
kVA 2.08 2.08
Power Loss HO [W] 58 58
Power...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 1212519 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.