

INDUSTRIAL COMPONENT DATA

131F7838**FC-102P55KT4E55H2XGX1XXSXXXXXAXBXCXXXXDX****DANFOSS DRIVES****FC-102P55KT4E55H2XGX1XXSXXXXXAXBXCXXXXDX**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 1212519



Manufacturer	DANFOSS DRIVES
MPN / Reference	1212519
Catalog number	1212519
Category	VLT FC102 HVAC
Minimum order	1 unit
Document ID	EO-233CA6DAD3
Generated	2026-08-06

Product Overview

131F7838 FC-102P55KT4E55H2XGX1XXSXXXXXAXBXCXXXXDX DANFOSS DRIVES
FC-102P55KT4E55H2XGX1XXSXXXXXAXBXCXXXXDX

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS DRIVES > VLT FC102 HVAC - DANFOSS DRIVES

Additional Product Information

Frequency Converter
FC-102P55KT4E55H2XGX1XXSXXXXXAXBXCXXXXDX
VLT® HVAC Drive FC-102
(P55K) 55 KW / 75 HP,
Three phase, 380 - 480 VAC, IP55 / Type 12
RFI Filter
No brake chopper
Graphical Loc. Cont. Panel
Not coated PCB, Mains Disconnect
Latest release std. SW.
Frame: C1

No A Option, No B Option
No C1 option, No D option
Other options according to Model Code
Product details
Gross weight 42.31 Kilogram
Net weight 39.31 Kilogram
Volume 176.054 Liter
EAN 5702427478190
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® HVAC Drive FC-
Series 102 102
Power Rating P55K (P55K) 55 KW / 75 HP
Phase T Three phase
Mains Voltage 4 380 - 480 VAC
Enclosure E55 IP55 / Type 12
RFI Filter H2 RFI Filter
Brake - Safe Stop X No brake chopper
LCP G Graphical Loc. Cont. Panel
Coating PCB X Not coated PCB
Mains Option 1 Mains Disconnect
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AX No A Option
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size C1 C1
Product Catalog NO_VIEW NO VIEW
Typecode Part 1 FC-102P55KT4E55H2XGX
Typecode Part 2 1XXSXXXXAXBXCXXXXDX
Power 110% (NO) [KW] 55 55
Height [mm] 685,0 685,0
Width w/ no C options [mm] 308,0 308,0
Depth [mm] 311,0 311,0
Depth with Option A/B [mm] 311,0 311,0
kVA 73.4 73.4
Power Loss NO [W] 1083 1083
Power Loss NO [...]

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 1212519 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.