

## INDUSTRIAL COMPONENT DATA

**131U2341****FC-202PK37T4E20H2XGXXXXSXXXXAQBXCXXXXDX****DANFOSS DRIVES VLT AQUA Drive FC-202 0.37 KW / 0.50 HP, 380..**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 131U2341



|                 |                |
|-----------------|----------------|
| Manufacturer    | DANFOSS DRIVES |
| MPN / Reference | 131U2341       |
| Catalog number  | 131U2341       |
| Category        | VLT AQUA FC202 |
| Minimum order   | 1 unit         |
| Document ID     | EO-B5A3B68ACF  |
| Generated       | 2026-08-06     |

## Product Overview

131U2341 FC-202PK37T4E20H2XGXXXXSXXXXAQBXCXXXXDX DANFOSS DRIVES VLT AQUA Drive FC-202 0.37 KW / 0.50 HP, 380..

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                  |
|--------------|--------------------------------------------------|
| Catalog path | DANFOSS DRIVES > VLT AQUA FC202 - DANFOSS DRIVES |
|--------------|--------------------------------------------------|

## Additional Product Information

Frequency converter

FC-202PK37T4E20H2XGXXXXSXXXXAQBXCXXXXDX

VLT® AQUA Drive FC-202

(PK37) 0.37 KW / 0.50 HP,

Three phase, 380 - 480 VAC, (E20) IP20 / Chassis

RFI Filter

No brake chopper

Graphical Loc. Cont. Panel

Not coated PCB, No Mains Option

Latest release std. SW.

Frame: A2

Modbus TCP MCA 122, No B Option  
No C1 option, No D option  
Other options according to Model code  
Product details  
Gross weight 4.886 Kilogram  
Net weight 4.04 Kilogram  
Volume 21.569 Liter  
EAN 5702427934221  
Product View (Switch) GLBL Global (Standard)  
Product Group FC- VLT® AQUA Drive FC-  
Series 202 202  
Power Rating PK37 (PK37) 0.37 KW / 0.50 HP  
Phase T Three phase  
Mains Voltage 4 380 - 480 VAC  
Enclosure E20 (E20) IP20 / Chassis  
RFI Filter H2 RFI Filter  
Brake - Safe Stop X No brake chopper  
LCP G Graphical Loc. Cont. Panel  
Coating PCB X Not coated PCB  
Mains Option X No Mains Option  
Adaptation A X Standard Cable Entries  
Adaptation B X No adaptation  
Software Release SXXX Latest release std. SW.  
Software Language Pack X Standard Language Pack  
A Option AQ Modbus TCP MCA 122  
B Option BX No B Option  
C0 Option MCO CX No C0 option  
C1 Option X No C1 option  
C Option Software XX No software option  
D Option DX No D option  
Frame Size A2 A2  
Typecode Part 1 FC-202PK37T4E20H2XGX  
Typecode Part 2 XXXSXXXXAQBXCXXXXDX  
Product Catalog NO\_VIEW NO VIEW  
Power 150% (HO) [KW] 0.37 0.37  
Power 110% (NO) [KW] 0.37 0.37  
Height [mm] 268,0 268,0  
Width w/ no C options [mm] 90,0 90,0  
Width w/ two C options [mm] 150,0 150,0  
Depth [mm] 205,0...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 131U2341 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.