

INDUSTRIAL COMPONENT DATA

132L3291**FC-102N132T4E5SH2TGC7XXSXXXXAXBXCXXXXDX****DANFOSS DRIVES VLT® HVAC Drive FC 100(102) HVAC****Versión Ava..**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 1212519



Manufacturer	DANFOSS DRIVES
MPN / Reference	1212519
Catalog number	1212519
Category	VLT FC102 HVAC
Minimum order	1 unit
Document ID	EO-C1DF25965C
Generated	2026-08-06

Product Overview

132L3291 FC-102N132T4E5SH2TGC7XXSXXXXAXBXCXXXXDX DANFOSS DRIVES VLT® HVAC Drive FC 100(102) HVAC Versión Ava..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS DRIVES > VLT FC102 HVAC - DANFOSS DRIVES

Additional Product Information

Frequency Converter

FC-102N132T4E5SH2TGC7XXSXXXXAXBXCXXXXDX

VLT® HVAC Drive FC-102

(N132) 132 KW / 200 HP,

Three phase, 380 - 480 VAC, IP54/Type12,N3R Rdy+Heat

RFI Filter

Safe Stop

Graphical Loc. Cont. Panel

Coated PCB, Fuse

Latest release std. SW.

Frame: D1H

No A Option, No B Option
No C1 option, No D option
Other options according to Model Code
Product details
Gross weight 62.3 Kilogram
Net weight 62 Kilogram
Volume 255.881 Liter
EAN 5714853426560
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® HVAC Drive FC-
Series 102 102
Power Rating N132 (N132) 132 KW / 200 HP
Phase T Three phase
Mains Voltage 4 380 - 480 VAC
Enclosure E5S IP54/Type12,N3R Rdy+Heat
RFI Filter H2 RFI Filter
Brake - Safe Stop T Safe Stop
LCP G Graphical Loc. Cont. Panel
Coating PCB C Coated PCB
Mains Option 7 Fuse
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AX No A Option
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size D1H D1H
Product Catalog NO_VIEW NO VIEW
Typecode Part 1 FC-102N132T4E5SH2TGC
Typecode Part 2 7XXSXXXXAXBXCXXXXDX
Power 110% (NO) [KW] 132 132
Height [mm] 901,0 901,0
Width w/ no C options [mm] 325,0 325,0
Depth [mm] 378,0 378,0
Depth with Option A/B [mm] 378,0 378,0
kVA 180 180
Power Loss NO [W] 2949 2949
Power Loss NO [W] 2719 2719
Continuous...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 1212519 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.