

INDUSTRIAL COMPONENT DATA

134F3130**FC-202PK55T4E20H3TNXXXXSXXXXAXBXCXXXXDX****DANFOSS DRIVES VLT AQUA Drive FC-202 0.55 KW / 0.75 HP, 380..**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 134F3130



Manufacturer	DANFOSS DRIVES
MPN / Reference	134F3130
Catalog number	134F3130
Category	VLT AQUA FC202
Minimum order	1 unit
Document ID	EO-FF058107D1
Generated	2026-08-06

Product Overview

134F3130 FC-202PK55T4E20H3TNXXXXSXXXXAXBXCXXXXDX DANFOSS DRIVES VLT AQUA Drive FC-202 0.55 KW / 0.75 HP, 380..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	DANFOSS DRIVES > VLT AQUA FC202 - DANFOSS DRIVES
--------------	--

Additional Product Information

Frequency converter

FC-202PK55T4E20H3TNXXXXSXXXXAXBXCXXXXDX

VLT® AQUA Drive FC-202

0.55 KW / 0.75 HP,

Three phase, 380 - 480 VAC, (E20) IP20 / Chassis

(H3) RFI Class A1/B (C1)

Safe Stop

Numerical Loc. Cont. Panel

Not coated PCB, No Mains Option

Latest release std. SW.

Frame: A2

No A Option, No B Option
No C1 option, No D option
Other options according to Model code
Product details
Gross weight 5.216 Kilogram
Net weight 4.37 Kilogram
Volume 21.569 Liter
EAN 5710107428793
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® AQUA Drive FC-
Series 202 202
Power Rating PK55 0.55 KW / 0.75 HP
Phase T Three phase
Mains Voltage 4 380 - 480 VAC
Enclosure E20 (E20) IP20 / Chassis
RFI Filter H3 (H3) RFI Class A1/B (C1)
Brake - Safe Stop T Safe Stop
LCP N Numerical Loc. Cont. Panel
Coating PCB X Not coated PCB
Mains Option X No Mains Option
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AX No A Option
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size A2 A2
Typecode Part 1 FC-202PK55T4E20H3TNX
Typecode Part 2 XXXSXXXAXBXCXXXDX
Product Catalog NO_VIEW NO VIEW
Power 150% (HO) [KW] 0.55 0.55
Power 110% (NO) [KW] 0.55 0.55
Height [mm] 268,0 268,0
Width w/ no C options [mm] 90,0 90,0
Width w/ two C options [mm] 150,0 150,0
Depth [mm] 205,0 205,0
Depth w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 134F3130 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.