

INDUSTRIAL COMPONENT DATA

134F9028**FC-103P3K0T4E55H2XGXXXXSXXXXAXBXCXXXXDX****DANFOSS DRIVES****FC-103P3K0T4E55H2XGXXXXSXXXXAXBXCXXXXDX**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 1212519



Manufacturer	DANFOSS DRIVES
MPN / Reference	1212519
Catalog number	1212519
Category	VLTA Refrigeration Drive
Minimum order	1 unit
Document ID	EO-A7A0A33549
Generated	2026-08-04

Product Overview

134F9028 FC-103P3K0T4E55H2XGXXXXSXXXXAXBXCXXXXDX DANFOSS DRIVES
FC-103P3K0T4E55H2XGXXXXSXXXXAXBXCXXXXDX

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS DRIVES > VLTA Refrigeration Drive

Additional Product Information

Frequency converter
FC-103P3K0T4E55H2XGXXXXSXXXXAXBXCXXXXDX
VLT® Refrigeration Drive FC-103
3.0 KW / 4.0 HP,
Three phase, 380 - 480 VAC, IP55 / Type 12
RFI filter Class A2
No brake chopper
Graphical Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
No A Option, No B Option

No C1 option, No D option

Frame: A5

Other options according to Model code

Product details

Gross weight 11.206 Kilogram

Net weight 10.59 Kilogram

Volume 39.798 Liter

EAN 5710107493180

Product View (Switch) GLBL Global (Standard)

Product Group FC- VLT® Refrigeration Drive

Series 103 103

Power Rating P3K0 3.0 KW / 4.0 HP

Phase T Three phase

Mains Voltage 4 380 - 480 VAC

Enclosure E55 IP55 / Type 12

RFI Filter H2 RFI filter Class A2

Brake - Safe Stop X No brake chopper

LCP G Graphical Loc. Cont. Panel

Coating PCB X Not coated PCB

Mains Option X No Mains Option

Adaptation A X Standard Cable Entries

Adaptation B X No adaptation

Software Release SXXX Latest release std. SW.

Software Language Pack X Standard Language Pack

A Option AX No A Option

B Option BX No B Option

C0 Option MCO CX No C0 option

C1 Option X No C1 option

C Option Software XX No software option

D Option DX No D option

Frame Size A5 A5

Product Catalog NO_VIEW NO VIEW

Typecode Part 1 FC-103P3K0T4E55H2XGX

Typecode Part 2 XXXSXXXAXBXCXXXDX

Power 110% (NO) [KW] 3 3

Height [mm] 420,0 420,0

Width w/ no C options [mm] 242,0 242,0

Depth [mm] 200,0 200,0

Depth with Option A/B [mm] 200,0 200,0

kVA 4.99 4.99

Power Loss NO [W] 116 116...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 1212519 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.