

INDUSTRIAL COMPONENT DATA

134N5104**FC-202PK55T4E20H1XGCXXXSXXXALBXCXXXDX****DANFOSS DRIVES VLT AQUA Drive FC-202 0.55 KW / 0.75 HP, 380..**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 134N5104



Manufacturer	DANFOSS DRIVES
MPN / Reference	134N5104
Catalog number	134N5104
Category	VLT AQUA FC202
Minimum order	1 unit
Document ID	EO-63822613B9
Generated	2026-08-06

Product Overview

134N5104 FC-202PK55T4E20H1XGCXXXSXXXALBXCXXXDX DANFOSS DRIVES VLT AQUA Drive FC-202 0.55 KW / 0.75 HP, 380..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS DRIVES > VLT AQUA FC202 - DANFOSS DRIVES

Additional Product Information

Frequency converter
FC-202PK55T4E20H1XGCXXXSXXXALBXCXXXDX
VLT® AQUA Drive FC-202
0.55 KW / 0.75 HP,
Three phase, 380 - 480 VAC, (E20) IP20 / Chassis
(H1) RFI Class A1/B (C1)
No brake chopper
Graphical Loc. Cont. Panel
Coated PCB, No Mains Option
Latest release std. SW.
Frame: A2

PROFINET MCA 120, No B Option
No C1 option, No D option
Other options according to Model code
Product details
Gross weight 5.386 Kilogram
Net weight 4.54 Kilogram
Volume 21.569 Liter
EAN 5710107903566
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® AQUA Drive FC-
Series 202 202
Power Rating PK55 0.55 KW / 0.75 HP
Phase T Three phase
Mains Voltage 4 380 - 480 VAC
Enclosure E20 (E20) IP20 / Chassis
RFI Filter H1 (H1) RFI Class A1/B (C1)
Brake - Safe Stop X No brake chopper
LCP G Graphical Loc. Cont. Panel
Coating PCB C Coated PCB
Mains Option X No Mains Option
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AL PROFINET MCA 120
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size A2 A2
Typecode Part 1 FC-202PK55T4E20H1XGC
Typecode Part 2 XXXSXXXXALBXCXXXXDX
Product Catalog GLBL Global (Standard)
Power 150% (HO) [KW] 0.55 0.55
Power 110% (NO) [KW] 0.55 0.55
Height [mm] 268,0 268,0
Width w/ no C options [mm] 90,0 90,0
Width w/ two C options [mm] 150,0 150,0
Depth [...]

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 134N5104 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.