

INDUSTRIAL COMPONENT DATA

**134U3937 FC-202PK55T4E20H3TXXXXXSXXXXALBXCXXXXD0
DANFOSS DRIVES VLT AQUA Drive FC-202 0.55 KW / 0.75 HP,
380..**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 134U3937



Manufacturer	DANFOSS DRIVES
MPN / Reference	134U3937
Catalog number	134U3937
Category	VLT AQUA FC202
Minimum order	1 unit
Document ID	EO-5374A55227
Generated	2026-08-06

Product Overview

134U3937 FC-202PK55T4E20H3TXXXXXSXXXXALBXCXXXXD0 DANFOSS DRIVES VLT AQUA Drive FC-202 0.55 KW / 0.75 HP, 380..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	DANFOSS DRIVES > VLT AQUA FC202 - DANFOSS DRIVES
--------------	--

Additional Product Information

Frequency converter
FC-202PK55T4E20H3TXXXXXSXXXXALBXCXXXXD0
VLT® AQUA Drive FC-202
0.55 KW / 0.75 HP,
Three phase, 380 - 480 VAC, (E20) IP20 / Chassis
(H3) RFI Class A1/B (C1)
Safe Stop
No Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
Frame: A2
PROFINET MCA 120, No B Option

No C1 option, MCB-107 24V DC backup
Other options according to Model code
Product details
Gross weight 5.346 Kilogram
Net weight 4.5 Kilogram
Volume 21.569 Liter
EAN 5710107999620
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® AQUA Drive FC-
Series 202 202
Power Rating PK55 0.55 KW / 0.75 HP
Phase T Three phase
Mains Voltage 4 380 - 480 VAC
Enclosure E20 (E20) IP20 / Chassis
RFI Filter H3 (H3) RFI Class A1/B (C1)
Brake - Safe Stop T Safe Stop
LCP X No Loc. Cont. Panel
Coating PCB X Not coated PCB
Mains Option X No Mains Option
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AL PROFINET MCA 120
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option D0 MCB-107 24V DC backup
Frame Size A2 A2
Typecode Part 1 FC-202PK55T4E20H3TXX
Typecode Part 2 XXXSXXXXALBXCXXXXD0
Product Catalog GLBL Global (Standard)
Power 150% (HO) [KW] 0.55 0.55
Power 110% (NO) [KW] 0.55 0.55
Height [mm] 268,0 268,0
Width w/ no C options [mm] 90,0 90,0
Width w/ two C options [mm] 150,0 150,0
Depth [m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 134U3937 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.