

INDUSTRIAL COMPONENT DATA

175U0987 DANFOSS DRIVES Brake resistor 3HP, 460V, 5% duty cycle

Brand: DANFOSS DRIVES | Manufacturer Part Number: 175U0987



Manufacturer	DANFOSS DRIVES
MPN / Reference	175U0987
Catalog number	175U0987
Category	OPTIONS AND ACCESSORIES FC302 FC202 FC102
Minimum order	1 unit
Document ID	EO-30EEB881CA
Generated	2026-08-03

Product Overview

175U0987 DANFOSS DRIVES Brake resistor 3HP, 460V, 5% duty cycle

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	DANFOSS DRIVES > OPTIONS AND ACCESSORIES FC302 FC202 FC102 - DANFOSS DRIVES
--------------	---

Additional Product Information

Type: BWD500210 for VLT types: FCD322 / 2815 (380-480V) / 5004 (380-500V) / FC300 PK55 (200-240V) / FC300P2K2 (380-480 / 500V) (here in after general technical data on the braking resistor, Duty cycle / braking power depends on the frequency converter

Nominal power: 200W

Resistance value: 210Ohm

Braking power:

40% ED / cycle time 120s 400W

30% ED / cycle time 120s 500W

20% ED / cycle time 120s 700W

10% ED / cycle time 120s 1200W

5% ED / cycle time 120s 2000W

2% ED / cycle time 120s 4000W

Degree of protection: IP65

Dimensions HxWxD: 216 x 80 x 15mm

Weight: 0.6kg

Product details

Gross weight 0.55 Kilogram

Net weight 0.55 Kilogram

Volume 0.415 Liter

EAN 5702427041431

Gross weight 0.55 Kilogram

Net weight 0.55 Kilogram

Volume 0.415 Liter

EAN 5702427041431

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 175U0987 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.