

INDUSTRIAL COMPONENT DATA

**134U2983 FC-280P3K0T4E20H1BXCXXXSXXXXXAX DANFOSS
DRIVES FC-280P3K0T4E20H1BXCXXXSXXXXXAX VLT®Midi
Drive FC 280 ..**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 134U2983



Manufacturer	DANFOSS DRIVES
MPN / Reference	134U2983
Catalog number	134U2983
Category	VLTA Midi Drive FC 280
Minimum order	1 unit
Document ID	EO-B167C34F13
Generated	2026-08-06

Product Overview

134U2983 FC-280P3K0T4E20H1BXCXXXSXXXXXAX DANFOSS DRIVES FC-280P3K0T4E20H1BXCXXXSXXXXXAX
VLT®Midi Drive FC 280 ..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	DANFOSS DRIVES > VLTA Midi Drive FC 280
--------------	---

Additional Product Information

Frequency converter
FC-280P3K0T4E20H1BXCXXXSXXXXXAX
VLT® Midi Drive FC-280
3.0 kW / 4.0 HP, Three phase 380-480 VAC
IP20 / Chassis, EMC Cat C1(200V)/C2(400V)
Brake chopper, No display
Coated PCB, Latest release
Standard w. Modbus
Frame: K2
Other options according to Model code
Product details
Gross weight 4.39 Kilogram

Net weight 3.87 Kilogram
Volume 22.04 Liter
EAN 5710107990023
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® Midi Drive FC-
Series 280 280
Power Size P3K0 3.0 kW / 4.0 HP
Voltage T4 Three phase 380-480 VAC
Enclosure E20 IP20 / Chassis
RFI Filter H1 EMC Cat C1(200V)/C2(400V)
Brake & Stop B Brake chopper
Display X No display
Coating C Coated PCB
Mains Option X No mains options
Adaptation A X No Adaption
Adaptation B X No Adaption
Special Version SXXX Latest release
Software Language Pack X Standard language pack
Control Card AX Standard w. Modbus
Frame Size K2 K2
Typecode Part 1 FC-280P3K0T4E20H1BXC
Typecode Part 2 XXXSXXXXAX
Product Catalog NO_VIEW NO VIEW
Calculated Gross Weight [kg] 3.9
Calculated Net Weight [kg] 3.6
Intermittent Current (HO) [A] 11.5 11.5
Intermittent Current (HO) [A] 11.5 11.5
Continuous Current (HO) [A] 7.2 7.2
Continuous Current (HO) [A] 6.3 6.3
Power Loss HO [W] 94.8 94.8
kVA 5.0 5.0
Power 160% (HO) [KW] 3 3
Height [mm] 272.5 272.5
Width w/ no C options [mm] 90.0 90.0
Depth [mm] 168.0 168.0
Vendor ERR01 Cannot Determine Vendor
Producing plant ERR01 Cannot Determine Vendor
Modelcode01 FC-280P3K0T4E20H1BXC
Modelcode02 X...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 134U2983 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.