

INDUSTRIAL COMPONENT DATA

131F2372 DANFOSS DRIVES VLT Automation Drive FC 300 315 KW / 450 HP, 380-500 VAC, IP54 / Type 12, RFI class ..

Brand: DANFOSS DRIVES | Manufacturer Part Number: 131F2372



Manufacturer	DANFOSS DRIVES
MPN / Reference	131F2372
Catalog number	131F2372
Category	VLT AUTOMATIONDRIVE FC-302 P GREATER POWER THAN 30kW
Minimum order	1 unit
Document ID	EO-96AB74A2EC
Generated	2026-08-06

Product Overview

131F2372 DANFOSS DRIVES VLT Automation Drive FC 300 315 KW / 450 HP, 380-500 VAC, IP54 / Type 12, RFI class ..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS DRIVES > VLT AUTOMATIONDRIVE FC-302 P GREATER POWER THAN 30kW

Additional Product Information

Product details

Gross weight 393 kg

Net weight 284 kg

Volume 0 l

EAN 5702427419070

VLT® AUTOMATIONDRIVE FC 300 SERIES

Product View (Switch) GLBL Global (Standard)

Product Group FC- VLT® AutomationDrive FC-Series 302 302

Power Rating P315 (P315) 315 KW / 450 HP

Phase T Three phase

Mains Voltage 5 380 - 500 VAC

Enclosure E54 (E54) IP54 / Type 12

RFI Filter H4 RFI class A1 (C2)

Brake - Safe Stop B Brake chopper

LCP G Graphical Loc. Cont. Panel
Coating PCB C Coated PCB
Mains Option X No Mains Option
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AX No A Option
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size E1 E1
Typecode Part 1 FC-302P315T5E54H4BGC
Typecode Part 2 XXXSXXXAXBXCXXXDX
Product Catalog NO_VIEW NO VIEW
Power 150% (HO) [KW] 315
Power 110% (NO) [KW] 355
Height [mm] 2000,0
Width w/ no C options [mm] 600,0
Depth [mm] 494,0
Depth with Option A/B [mm] 494,0
kVA 416
Power Loss NO [W] 7532
Power Loss NO [W] 6724
Power Loss HO [W] 6794
Power Loss HO [W] 6118
Continuous Current (NO) [A] 658
Intermittent Current (NO) [A] 724
Continuous Current (NO) [A] 590
Intermittent Current (NO) [A] 649
Continuous Current (HO) [A] 600
Intermittent Current (HO) [A] 900
Continuous Current (HO) [A] 540
Intermittent Current (HO) [A] 810
Calculated Gross Weight [kg] 27...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 131F2372 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.