

INDUSTRIAL COMPONENT DATA

131B0100**FC-302P4K0T5E20H2XXXXXXXXSXXXXAXBXCXXXXDX****DANFOSS DRIVES VLT Automation Drive FC 300 4.0 KW / 5.5 HP,..**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 131B0100



Manufacturer	DANFOSS DRIVES
MPN / Reference	131B0100
Catalog number	131B0100
Category	VLT AUTOMATIONDRIVE FC 302
Minimum order	1 unit
Document ID	EO-EA53E7C595
Generated	2026-08-06

Product Overview

131B0100 FC-302P4K0T5E20H2XXXXXXXXSXXXXAXBXCXXXXDX DANFOSS DRIVES VLT Automation Drive FC 300 4.0 KW / 5.5 HP,..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS DRIVES > VLT AUTOMATIONDRIVE FC 302 - DANFOSS DRIVES

Additional Product Information

Frequency converter
FC-302P4K0T5E20H2XXXXXXXXSXXXXAXBXCXXXXDX
VLT® AutomationDrive FC-302
(P4K0) 4.0 KW / 5.0 HP,
Three phase, 380 - 500 VAC, (E20) IP20 / Chassis
RFI Filter
No brake chopper
No Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
Frame: A2

No A Option, No B Option
No C1 option, No D option
Other options according to Model code
Product details
Gross weight 4.846 Kilogram
Net weight 4 Kilogram
Volume 21.569 Liter
EAN 5702427105263
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® AutomationDrive FC-
Series 302 302
Power Rating P4K0 (P4K0) 4.0 KW / 5.0 HP
Phase T Three phase
Mains Voltage 5 380 - 500 VAC
Enclosure E20 (E20) IP20 / Chassis
RFI Filter H2 RFI Filter
Brake - Safe Stop X No brake chopper
LCP X No Loc. Cont. Panel
Coating PCB X Not coated PCB
Mains Option X No Mains Option
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AX No A Option
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size A2 A2
Typecode Part 1 FC-302P4K0T5E20H2XXX
Typecode Part 2 XXXSXXXXAXBXCXXXXDX
Product Catalog NO_VIEW NO VIEW
Power 160% (HO) [KW] 4 4
Height [mm] 268,0 268,0
Width w/ no C options [mm] 90,0 90,0
Width w/ two C options [mm] 150,0 150,0
Depth [mm] 205,0 205,0
Depth with Option A/B [mm] 220,0 220,0
kVA 6.93 6.93
Po...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 131B0100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.