

INDUSTRIAL COMPONENT DATA

131F5449**FC-102P55KT4E20H2XGXXXXSXXXXAXBXCXXXXDX****DANFOSS DRIVES VLT® HVAC Drive FC 102 55 KW / 75 HP,
380 48..**

Brand: DANFOSS DRIVES | Manufacturer Part Number: 131F5449



Manufacturer	DANFOSS DRIVES
MPN / Reference	131F5449
Catalog number	131F5449
Category	VLT FC102 HVAC
Minimum order	1 unit
Document ID	EO-976B4532FB
Generated	2026-08-03

Product Overview

131F5449 FC-102P55KT4E20H2XGXXXXSXXXXAXBXCXXXXDX DANFOSS DRIVES VLT® HVAC Drive FC 102 55 KW / 75 HP, 380 48..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	DANFOSS DRIVES > VLT FC102 HVAC - DANFOSS DRIVES
--------------	--

Additional Product Information

Frequency Converter
FC-102P55KT4E20H2XGXXXXSXXXXAXBXCXXXXDX
VLT® HVAC Drive FC-102
(P55K) 55 KW / 75 HP,
Three phase, 380 - 480 VAC, (E20) IP20 / Chassis
RFI Filter
No brake chopper
Graphical Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
Frame: C3

No A Option, No B Option
No C1 option, No D option
Other options according to Model Code
Product details
Gross weight 35.94 Kilogram
Net weight 33.09 Kilogram
Volume 178.336 Liter
EAN 5702427452268
Product View (Switch) GLBL Global (Standard)
Product Group FC- VLT® HVAC Drive FC-
Series 102 102
Power Rating P55K (P55K) 55 KW / 75 HP
Phase T Three phase
Mains Voltage 4 380 - 480 VAC
Enclosure E20 (E20) IP20 / Chassis
RFI Filter H2 RFI Filter
Brake - Safe Stop X No brake chopper
LCP G Graphical Loc. Cont. Panel
Coating PCB X Not coated PCB
Mains Option X No Mains Option
Adaptation A X Standard Cable Entries
Adaptation B X No adaptation
Software Release SXXX Latest release std. SW.
Software Language Pack X Standard Language Pack
A Option AX No A Option
B Option BX No B Option
C0 Option MCO CX No C0 option
C1 Option X No C1 option
C Option Software XX No software option
D Option DX No D option
Frame Size C3 C3
Product Catalog NO_VIEW NO VIEW
Typecode Part 1 FC-102P55KT4E20H2XGX
Typecode Part 2 XXXSXXXAXBXCXXXDX
Power 110% (NO) [KW] 55 55
Height [mm] 550,0 550,0
Width w/ no C options [mm] 308,0 308,0
Depth [mm] 333,0 333,0
Depth with Option A/B [mm] 333,0 333,0
kVA 73.4 73.4
Power Loss NO [W] 1083 1083
Power...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS DRIVES / 131F5449 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.