

INDUSTRIAL COMPONENT DATA

TI 16C 047H0207 DANFOSS CONTROLES INDUSTRIALES TI 16C Overload relay 1,8 2,8A M/60

Brand: DANFOSS INDUSTRIAL AUTOMATION | Manufacturer Part Number: TI 16C



Manufacturer	DANFOSS INDUSTRIAL AUTOMATION
MPN / Reference	TI 16C
Catalog number	TI 16C
Category	Overload relay
Minimum order	1 unit
Document ID	EO-E4A17CE63F
Generated	2026-08-02

Product Overview

TI 16C 047H0207 DANFOSS CONTROLES INDUSTRIALES TI 16C Overload relay 1,8 2,8A M/60

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS INDUSTRIAL AUTOMATION > Overload relay - DANFOSS INDUSTRIAL AUTOMATION > TI 16C (serie 16

Additional Product Information

Current DOL motor starter [A] [min]: 1.8, Current DOL motor starter [A] [max]: 2.8

Product details

Gross weight 0.112 Kilogram

Net weight 0.108 Kilogram

Volume 0.233 Liter

EAN 5702423014293

Type TI 16C

Product group Contactors and motor starters

Product Name Description Overload relay

Gross weight 0.112 Kilogram

Net weight 0.108 Kilogram

Volume 0.233 Liter

EAN 5702423014293

Type TI 16C

Product group Contactors and motor starters

Product Name Description Overload relay
Approval CE
EAC
LLC CDC TYSK
UKCA
UL
CE mark Yes
China RoHS compliance Out of scope
Contains batteries No
Current DOL motor starter [A] [max] 2.8 A
Current DOL motor starter [A] [min] 1.8 A
Current. star-delta starter [A [max] 4.8 A
Current. star-delta starter [A [min] 3.2 A
EEE category 5 small equipment (any external dimension < 50 cm)
EU RoHS compliance Yes
EU RoHS exemption clause No
Identical product 047H4207
In scope of WEEE Yes
Packing format Multi pack
Quantity per packing format 10 pc
REACH Candidate List substances Lead (CAS no. 7439-92-1)
UL approval file name E82701
UL mark Yes
Approval CE
EAC
LLC CDC TYSK
UKCA
UL
CE mark Yes
China RoHS compliance Out of scope
Contains batteries No
Current DOL motor starter [A] [max] 2.8 A
Current DOL motor starter [A] [min] 1.8 A
Current. star-delta starter [A [max] 4.8 A
Current. star-delta starter [A [min] 3.2 A
EEE category 5 small equipment (any external dimension < 50 cm)
EU RoHS compliance Yes
EU RoHS exemption clause No
Identical product 047H4207
In scope of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS INDUSTRIAL AUTOMATION / TI 16C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.