

INDUSTRIAL COMPONENT DATA

EV210B 032U3653 DANFOSS CONTROLES INDUSTRIALES

Valve EV210B 3SS G 14E NC000

Brand: DANFOSS INDUSTRIAL AUTOMATION | Manufacturer Part Number: EV210B



Manufacturer	DANFOSS INDUSTRIAL AUTOMATION
MPN / Reference	EV210B
Catalog number	EV210B
Category	Industrial valves
Minimum order	1 unit
Document ID	EO-6B0DE5C98A
Generated	2026-08-01

Product Overview

EV210B 032U3653 DANFOSS CONTROLES INDUSTRIALES Valve EV210B 3SS G 14E NC000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS INDUSTRIAL AUTOMATION > Industrial valves - DANFOSS INDUSTRIAL AUTOMATION > Solenoid , 2

Additional Product Information

Media recommendations: Water & Brine, Body material: Stainless steel, Operation: Direct-operated, Number of ways: 2/2

Product details

Gross weight 0.286 Kilogram

Net weight 0.263 Kilogram

Volume 0.253 Liter

EAN 5702423180059

Type EV210B

Product group Solenoid valves

Product Name Description Solenoid valve

Gross weight 0.286 Kilogram

Net weight 0.263 Kilogram

Volume 0.253 Liter

EAN 5702423180059

Type EV210B

Product group Solenoid valves

Product Name Description Solenoid valve
Actuator B
Actuator size 13.5 mm
Actuator size [in] 0.53 in
Actuator system [mm] 13.5 mm
Ambient temperature max. [°C] 80 °C
Ambient temperature max. [°F] 176 °F
Application Closed and Drain
Body material Stainless steel
China RoHS compliance Yes
China RoHS exemption clause No
Connection Internal/External Internal
Connection material Stainless steel
Connection size [in] 1/4
Connection standard ISO 228-1
Connection type G
Contains batteries No
Cv value [gal/min] 0.35 gal/min
Differential pressure [bar] [max] 30 bar
Differential pressure [bar] [min] 0 bar
Differential pressure [psi] [max] 435 psi
Differential pressure [psi] [min] 0 psi
EEE category 5 small equipment (any external dimension < 50 cm)
Est. time to close, water [ms] 20 ms
Est. time to open, water [ms] 20 ms
EU RoHS compliance Yes
EU RoHS exemption clause No
Flow direction Single-flow
Flow direction indicator Embossed 1-way arrow
Fluid Group 1
Function NC
In scope of WEEE Yes
Kv value [m³/h] 0.3 m³/h
Max media viscosity [cSt] 50 cSt
Max. test p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS INDUSTRIAL AUTOMATION / EV210B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.