

INDUSTRIAL COMPONENT DATA

RT106 017-505066 DANFOSS CONTROLES INDUSTRIALES

RT106 Thermostat M/12

Brand: DANFOSS INDUSTRIAL AUTOMATION | Manufacturer Part Number: RT106



Manufacturer	DANFOSS INDUSTRIAL AUTOMATION
MPN / Reference	RT106
Catalog number	RT106
Category	Temperature switches
Minimum order	1 unit
Document ID	EO-9799996BAC
Generated	2026-08-01

Product Overview

RT106 017-505066 DANFOSS CONTROLES INDUSTRIALES RT106 Thermostat M/12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS INDUSTRIAL AUTOMATION > Temperature switches - DANFOSS INDUSTRIAL AUTOMATION > contr

Additional Product Information

Temperature range [°C]: 20 - 90, Reset function: Auto, Contact function: SPDT, Sensor type: Remote bulb, Capillary tube length [mm]: 5000, Enclosure rating IP: IP66

Product details

Gross weight 1.34 Kilogram

Net weight 1.228 Kilogram

Volume 3.443 Liter

EAN 5702423119547

Type RT106

Product group Switches and thermostats

Product Name Description Thermostat

Gross weight 1.34 Kilogram

Net weight 1.228 Kilogram

Volume 3.443 Liter

EAN 5702423119547

Type RT106

Product group Switches and thermostats

Product Name Description Thermostat

Ambient temperature range [°C] [max] 70 °C

Ambient temperature range [°C] [min] -50 °C

Ambient temperature range [°F] [max] 158 °F

Ambient temperature range [°F] [min] -58 °F

Approval CCC

CE

DNV

EAC

GL

LLC CDC EURO-TYSK

LR

LVD

NKK

RMRS

RoHS

RoHS China

TYSK

Cap. tube length fraction [in] 196 7/8 in

Capillary tube length [mm] 5000 mm

CE mark Yes

Charge type Cross-Ambient

China RoHS compliance Yes

Contact function SPDT

Contact rating AC15=3 A, 400 V

AC1=10 A, 400 V

AC3=4 A, 400 V

DC13=12 W, 220 V

LR=28 A, 400 V

Contains batteries No

Diff. @ Max. range setting[°C] [max] 7 °C

Diff. @ Max. range setting[°C] [min] 2 °C

Diff. @ Min. range setting[°C] [max] 20 °C

Diff. @ Min. range setting[°C] [min] 4 °C

Differential type Adjustable

Electrical conn. Male/Female Female

Electrical connection Screwed cable entry

Electrical connection size 2xPg 13.5

Electrical connection standard DIN 40430

Electrical spec. standard EN 60947-4/-5

EN 60947 electrical properties Insul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS INDUSTRIAL AUTOMATION / RT106 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.