

INDUSTRIAL COMPONENT DATA

RT107 017-513666 DANFOSS CONTROLES INDUSTRIALES

RT107 Thermostat M/15

Brand: DANFOSS INDUSTRIAL AUTOMATION | Manufacturer Part Number: RT107



Manufacturer	DANFOSS INDUSTRIAL AUTOMATION
MPN / Reference	RT107
Catalog number	RT107
Category	Temperature switches
Minimum order	1 unit
Document ID	EO-1048298E97
Generated	2026-07-29

Product Overview

RT107 017-513666 DANFOSS CONTROLES INDUSTRIALES RT107 Thermostat M/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS INDUSTRIAL AUTOMATION > Temperature switches - DANFOSS INDUSTRIAL AUTOMATION > contr

Additional Product Information

Temperature range [°C]: 70 - 150, Reset function: Manual Max, Contact function: SPDT, Sensor type: Remote bulb,
Capillary tube length [mm]: 2000, Enclosure rating IP: IP54

Product details

Gross weight 0.94 Kilogram

Net weight 0.818 Kilogram

Volume 2.685 Liter

EAN 5702423119622

Type RT107

Product group Switches and thermostats

Product Name Description Thermostat

Gross weight 0.94 Kilogram

Net weight 0.818 Kilogram

Volume 2.685 Liter

EAN 5702423119622

Type RT107

Product group Switches and thermostats

Product Name Description Thermostat

Ambient temperature range [°C] [max] 70 °C

Ambient temperature range [°C] [min] -50 °C

Ambient temperature range [°F] [max] 158 °F

Ambient temperature range [°F] [min] -58 °F

Approval CCC

CE

CMIM

DNV

EAC

GL

KR

LLC CDC EURO-TYSK

LR

LVD

NKK

RMRS

RoHS

RoHS China

TYSK

Cap. tube length fraction [in] 78 3/4 in

Capillary tube length [mm] 2000 mm

CE mark Yes

Charge type Partial

China RoHS compliance Yes

Contact function SPDT

Contact rating AC15=3 A, 400 V

AC1=10 A, 400 V

AC3=4 A, 400 V

DC13=12 W, 220 V

LR=28 A, 400 V

Contains batteries No

Diff. @ Max. range setting[°C] 1.8 °C

Diff. @ Min. range setting[°C] 6 °C

Differential type Fixed

Electrical conn. Male/Female Female

Electrical connection Screwed cable entry

Electrical connection size 2xPg 13.5

Electrical connection standard DIN 40430

Electrical spec. standard EN 60947-4/-5

EN 60947 electrical properties Insulation: 400V

Pollution degree: 3

Rated impulse voltage: 4 kV

Short circuit prot, fuse: 10A

EN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS INDUSTRIAL AUTOMATION / RT107 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.