

INDUSTRIAL COMPONENT DATA

RT107 017-513766 DANFOSS CONTROLES INDUSTRIALES

RT107 Thermostat M/15

Brand: DANFOSS INDUSTRIAL AUTOMATION | Manufacturer Part Number: RT107



Manufacturer	DANFOSS INDUSTRIAL AUTOMATION
MPN / Reference	RT107
Catalog number	RT107
Category	Temperature switches
Minimum order	1 unit
Document ID	EO-500E6F54D5
Generated	2026-08-04

Product Overview

RT107 017-513766 DANFOSS CONTROLES INDUSTRIALES RT107 Thermostat M/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path DANFOSS INDUSTRIAL AUTOMATION > Temperature switches - DANFOSS INDUSTRIAL AUTOMATION > contr

Additional Product Information

Temperature range [°C]: 70 - 150, Reset function: Auto, Contact function: SPDT, Sensor type: Remote bulb, Capillary tube length [mm]: 2000, Enclosure rating IP: IP66

Product details

Gross weight 0.96 Kg

Net weight 0.848 Kg

Volume 2.76 Liter

EAN 5702423119639

Gross weight 0.96 Kg

Net weight 0.848 Kg

Volume 2.76 Liter

EAN 5702423119639

Ambient temperature range [°C] [max] 70 °C

Ambient temperature range [°C] [min] -50 °C

Ambient temperature range [°F] [max] 158 °F

Ambient temperature range [°F] [min] -58 °F

Approval CCC

CE

DNV

EAC

GL

KR

LR

LVD

NKK

PZH

RMRS

RoHS

RoHS China

TYSK

CMIM

LLC CDC EURO-TYSK

UKCA

Cap. tube length fraction [in] 78 3/4 in

Capillary tube length [mm] 2000 mm

Charge type Partial

Contact function SPDT

Contact rating AC15=3 A, 400 V

AC1=10 A, 400 V

DC13=12 W, 220 V

AC3=4 A, 400 V

LR=28 A, 400 V

Diff. @ Max. range setting[°C] [max] 8 °C

Diff. @ Max. range setting[°C] [min] 1.8 °C

Diff. @ Min. range setting[°C] [max] 25 °C

Diff. @ Min. range setting[°C] [min] 6 °C

Differential type Adjustable

Electrical conn. Male/Female Female

Electrical connection Screwed cable entry

Electrical connection size 2xPg 13.5

Electrical connection standard DIN 40430

Electrical spec. standard EN 60947-4/-5

EN 60947 electrical properties Pollution degree: 3

Rated impulse voltage: 4 kV

Short circuit prot, fuse: 10A

Insulation: 400V

EN 60947 wiring properties Flex, ferrules: 0.2-1.5 mm²

Flex, no ferrules: 0.2-2.5 mm²

Solid/stranded: 0.2-2.5 mm²

Enclosure rating IP IP66

EU RoHS complian...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS INDUSTRIAL AUTOMATION / RT107 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.