


INDUSTRIAL COMPONENT DATA

061F8967 DANFOSS REFRIGERATION ACB Cartridge Switch 2UB230 I/300

Brand: DANFOSS REFRIGERATION | Manufacturer Part Number: 061F8967



Manufacturer	DANFOSS REFRIGERATION
MPN / Reference	061F8967
Catalog number	061F8967
Category	DANFOSS REFRIGERATION Products
Minimum order	300 units
Document ID	EO-D2E7EC965C
Generated	2026-08-01

Product Overview

061F8967 DANFOSS REFRIGERATION ACB Cartridge Switch 2UB230 I/300

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	DANFOSS REFRIGERATION
--------------	-----------------------

Additional Product Information

Higher activ. pressure [bar]: 42, Lower activ. pressure [bar]: 33, Reset function: Auto, Contact function: SPST(NC), Pressure connection type: Flare, Pressure connection size: 1/4 in, Electrical connection: Spade connectors, Enclosure rating IP: IP40

Product details

Gross weight 0.031 Kilogram

Net weight 0.03 Kilogram

Volume 0.069 Liter

EAN 5702428510172

Type ACB

Product group Switches and thermostats

Product Name Description Cartridge pressure switch

Gross weight 0.031 Kilogram

Net weight 0.03 Kilogram

Volume 0.069 Liter

EAN 5702428510172

Type ACB

Product group Switches and thermostats

Product Name Description Cartridge pressure switch

Ambient temperature range [°C] [max] 85 °C

Ambient temperature range [°C] [min] -30 °C

Ambient temperature range [°F] [max] 185 °F

Ambient temperature range [°F] [min] -20 °F

Burst pressure [bar] 200 bar

Burst pressure [psig] 2900 psig

CE mark Yes

China RoHS compliance Yes with exemptions

Contact function SPST(NC)

Contact rating AC=6 A, 250 V

Contains batteries No

Electrical connection Spade connectors

Enclosure rating IP IP40

EU RoHS compliance Yes with exemptions

EU RoHS exemption clause 6(c)

Higher activ. pressure [bar] 42 bar

Higher activ. pressure [psi] 609 psi

Housing Regular

Lower activ. pressure [bar] 33 bar

Lower activ. pressure [psi] 479 psi

Lubricants compatibility Oilfree applications

Max. Working Pressure [bar] 45 bar

Max. Working Pressure [psig] 653 psig

Medium temperature range [°C] [max] 135 °C

Medium temperature range [°C] [m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send DANFOSS REFRIGERATION / 061F8967 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.