

INDUSTRIAL COMPONENT DATA

FWH-.250A6F FWH--250A6F EATON ELECTRIC cartridge fuse, ultra rapid, 0.25 A, AC 500 V, 6 x 32 mm, aR, UL

Brand: EATON - MOELLER | Manufacturer Part Number: FWH-.250A6F



Manufacturer	EATON - MOELLER
MPN / Reference	FWH-.250A6F
Catalog number	FWH--250A6F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-5CADE86C54
Generated	2026-08-06

Product Overview

SEMI COND FUSE 0.25A 500V AC 6 X 32MM

FWH-.250A6F - Fuse-link, high speed, 0.25 A, AC 500 V, 6 x 32 mm, aR, UL

Fuse, Fuse-link, high speed, 0.25 A, AC 500 V, 6 x 32 mm, aR, UL, cylindrical, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 0.25 A, AC 500 V, 6 x 32 mm, aR, ULFuse, Fuse-link, high speed, 0.25 A, AC 500 V, 6 x 32 mm, aR, UL, cylindrical, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 50 kA

General specificationsProduct nameEaton Bussmann series high speed cylindrical fusePart

no.FWH-.250A6FEAN5027590499439Product Length/Depth33 millimetreProduct height7 millimetreProduct width7

millimetreProduct weight2.8 gramCompliancesRoHS Compliant

CE MarkedCertificationsCSA Certified

UL RecognizedProduct TradenameNoneProduct TypeHigh speed cylindrical fuseProduct Sub TypeNoneElectrical

dataAmperage Rating0.25 AVoltage rating700 VVoltage typeAC/DCInterrupt rating50 kAICClassClass aRClearing (I2T)0.05

at 500 VProduct specificationsApplicationSemiconductor, DC Common bus, DC drives, Power converters/rectifiersFuse

indicatorOtherTechnical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)Electric engineering, automation, process control

engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (
[AFZ796015])ModelCeramic fuseSizeOtherVoltage typeAC/DCRated current0.25 ARated voltage500 VUtilization
categoryaR (accompanied semiconductor protection)Rated operating frequency45 - 62 HzType of fuse status
indicatorOtherRelease characteristicOtherBreaking capacity50 kAPower loss at rated current2.7 W
ETIM for FWH-.250A6F Circuit breakers and fuses (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FWH-.250A6F with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.