

INDUSTRIAL COMPONENT DATA

100M125 415V AC BS88 FUSE CEO100M125 EATON ELECTRIC Utility fuse-link, low voltage, 50 A, AC 415 V, BS88/J, ..

Brand: EATON - MOELLER | Manufacturer Part Number: 100M125 415V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	100M125 415V AC BS88 FUSE
Catalog number	CEO100M125
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-C4CECE3894
Generated	2026-08-06

Product Overview

Utility fuse-link, low voltage, 50 A, AC 415 V, BS88/J, 31 x 131 mm, gL/gG, BS

100M125 415V AC BS88 FUSE

Eaton Bussmann series low voltage British standard fuse, Fuse-link, LV, 100 A, AC 415 V, BS88/A4, 27 x 110 mm, gM, BS, 100M125

Fuse, Fuse-link, low voltage, 100 A, AC 415 V, BS88/A4, 27 x 110 mm, gM, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder RS100H

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number CEO100M125 EAN

5027590496254 UPC 051712839426 Product Length/Depth 111 mm Product Height 28 mm Product Width 28 mm Product

Weight 102.4 g Compliances Contact Manufacturer Electrical data

Amperage Rating 125 A Voltage rating 415 V Voltage type AC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for RS100 Red spot fuse holder Product specifications

Fuse type CEO Fitted with: Offset bolted tags Construction BS88/A4

ETIM for CEO100M125 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A4

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current (EF000227)

125 A

Utilization category according to IEC 60269 (EF002572)

gM (motor protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

6.5 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

93.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 100M125 415V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.