

INDUSTRIAL COMPONENT DATA

100M125 415V AC BS88 gM FUSE OSD100M125 EATON ELECTRIC Fuse-link, low voltage, AC 415 V, BS88/B1, 31 x 136 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 100M125 415V AC BS88 gM FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	100M125 415V AC BS88 gM FUSE
Catalog number	OSD100M125
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-3791EEEACB
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, AC 415 V, BS88/B1, 31 x 136 mm, gM, BS

100M125 415V AC BS88 gM FUSE

Fuse-link, LV, 100 A, AC 415 V, BS88, 26 x 95 mm, gM, BS, 100M125

Fuse, Fuse-link, low voltage, 100 A, AC 415 V, BS88, 26 x 95 mm, gM, BS, offset bolted tags, general industrial applications, BS88, IEC 60269, Breaking Capacity 80 kA, Optional accessories fuse-holder CM100F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number OSD100M125 EAN

5027590505116 UPC 051712844413 Product Length/Depth 91 mm Product Height 27 mm Product Width 27 mm Product

Weight 81.9 g Compliances RoHS Compliant Electrical data

Amperage Rating 100 A Voltage rating 415 V Voltage type AC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for CM100F Red spot fuse holder

SC100 Safeclip fuse holder Product specifications

Fuse type OSD Fitted with: Offset bolted tags Construction BS88

ETIM for OSD100M125 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current (EF000227)

100 A

Utilization category according to IEC 60269 (EF002572)

gM (motor protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

6.5 W

Mounting holes (EF021553)

M5

Centre-to-centre distance of connections (EF021151)

73 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 100M125 415V AC BS88 gM FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.