

INDUSTRIAL COMPONENT DATA

100MJ29-6 EATON ELECTRIC Utility fuse-link, low voltage, 315 A, AC 415 V, BS88/J, 38 x 110 mm, gL/gG, BS, 82..

Brand: EATON - MOELLER | Manufacturer Part Number: 100MJ29-6



Manufacturer	EATON - MOELLER
MPN / Reference	100MJ29-6
Catalog number	100MJ296
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-EB2B5BC518
Generated	2026-08-06

Product Overview

100A 415V AC BS88 FUSE FEEDER PILLAR

Utility fuse-link, LV, 100 A, AC 415 V, BS88/J, 38 x 101 mm, gU, BS, 76mm fixing centres

Fuse, Utility fuse-link, low voltage, 100 A, AC 415 V, BS88/J, 38 x 101 mm, gU, BS, dual bolted tags (slotted), 76mm fixing centres, feeder pillars, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number 100MJ29-6 EAN 5027590427845

Product Length/Depth 101 mm Product Height 38 mm Product Width 38 mm Product Weight 181.8 g Compliances CE

Marked

RoHS Compliant Certifications BS

IEC 60269

EAC Electrical data

Amperage Rating 100 A Voltage rating 415 V Voltage type AC Breaking capacity 80 kA Product specifications

Fuse type MJ29 Fitted with: Slotted tags Construction BS88/J

ETIM for 100MJ29-6 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
J
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
415 V
Rated current (EF000227)
100 A
Utilization category according to IEC 60269 (EF002572)
gU (utility/distribution protection)
Breaking capacity (EF005617)
80 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
8 W
Mounting holes (EF021553)
M10
Centre-to-centre distance of connections (EF021151)
76 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 100MJ29-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.