

INDUSTRIAL COMPONENT DATA

BF-O-5/165-C 103092 EATON ELECTRIC Complete surface-mounted flat distribution board, white, 33 SU per row, 5..

Brand: EATON - MOELLER | Manufacturer Part Number: BF-O-5/165-C



Manufacturer	EATON - MOELLER
MPN / Reference	BF-O-5/165-C
Catalog number	103092
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-29C7896055
Generated	2026-08-02

Product Overview

Complete surface-mounted flat distribution board, white, 33 SU per row, 5 rows, type C

Complete BF-O-./.-C surface-mounted slim distribution board, white RAL 9016, 33 space units per row, 5 rows, height 900mm, width 705 mm, depth 140 mm, including door, front plates, DIN-rail mounting frame and neutral/PE terminals.

Enclosure: closed design, including back plate, back plate can be used as a fixing plane, knockout cable entry openings on the bottom, terminals pre-assembled on enclosure (no loss of space units). Wall trough with door frame, back plate can be used as a fixing plane, cable entry openings that are easy to knock out, 127 mm depth, terminals pre-assembled on enclosure (no loss of space units) , 4 side fixing brackets. Sheet steel door with cam lock included as standard, sheet steel door with expanded depth (required, for example, in order to install RMQ components in the door) (BFZ-OTR-./...) is available as an accessory. Removable DIN-rail mounting frame, for 45 mm modular installation devices, 150 mm DIN busbar distance, Eaton circuit-breakers can be integrated with installation kit, a universal mounting plate can be installed using an installation kit for surface-mounted enclosures (BFZ-O-ITMPL..). electrical contact for metal front plate achieved with special lock on enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Compact Distribution Boxes**

Additional Product Information

Complete surface-mounted flat distribution board, white, 33 SU per row, 5 rows, type C Complete BF-O-./.-C surface-mounted slim distribution board, white RAL 9016, 33 space units per row, 5 rows, height 900mm, width 705 mm,

depth 140 mm, including door, front plates, DIN-rail mounting frame and neutral/PE terminals. Enclosure: closed design, including back plate, back plate can be used as a fixing plane, knockout cable entry openings on the bottom, terminals pre-assembled on enclosure (no loss of space units). Wall trough with door frame, back plate can be used as a fixing plane, cable entry openings that are easy to knock out, 127 mm depth, terminals pre-assembled on enclosure (no loss of space units), 4 side fixing brackets. Sheet steel door with cam lock included as standard, sheet steel door with expanded depth (required, for example, in order to install RMQ components in the door) (BFZ-OTR-./...) is available as an accessory. Removable DIN-rail mounting frame, for 45 mm modular installation devices, 150 mm DIN busbar distance, Eaton circuit-breakers can be integrated with installation kit, a universal mounting plate can be installed using an installation kit for surface-mounted enclosures (BFZ-O-ITMPL...). electrical contact for metal front plate achieved with special lock on enclosure [Delivery program

Basic function Basic device Product function Installation distribution boards Product range BF flat DBO Design Surface mounted Installation site Indoor Type of installa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BF-O-5/165-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.