

INDUSTRIAL COMPONENT DATA

10HD36 EATON ELECTRIC Fuse-link, high speed, 10 A, AC 750 V, DC 750 V, 20 x 127 mm, aR, IEC

Brand: EATON - MOELLER | Manufacturer Part Number: 10HD36



Manufacturer	EATON - MOELLER
MPN / Reference	10HD36
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-66158F2C23
Generated	2026-08-06

Product Overview

10AMP FUSE 1200V ac 750V dc INDUST. FUSE

10HD36 - Fuse-link, high speed, 10 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS

Fuse, Fuse-link, high speed, 10 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS, offset bolted tags (slotted), traction, BS, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, high speed, 10 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS Fuse, Fuse-link, high speed, 10 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS, offset bolted tags (slotted), traction, BS, Breaking Capacity 80 kA

General specifications Product name Eaton Bussmann series high speed traction fuse Part

no. 10HD36 EAN 5027590428736 Product Length/Depth 118 millimetre Product height 48 millimetre Product width 145

millimetre Product weight 93.4 gram Compliances RoHS Compliant Certifications BS Product Tradename None Product

Type High speed traction fuse Product Sub Type None Electrical data Amperage Rating 10 A Voltage rating 1200 V Product

specifications Application traction Fuse indicator None Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) Electric engineering, automation, process control

engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) ()

[BAB264011]) Fuse construction type according to IEC 60269 Other Type of current AC/DC Rated voltage AC 1,200 V Rated

voltage DC 750 V Rated current 10 A Utilization category gL/gG (cable protection/equipment protection) Breaking capacity 80

kA Colour code None Type of fuse status indicator None Power loss at rated current 2.2 W Mounting holes M5 Centre-to-centre

distance of connections 122.4 mm

ETIM for 10HD36 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 10HD36 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.