

INDUSTRIAL COMPONENT DATA

110Amp 690Vac TYPE T FUSE 110CEET EATON ELECTRIC cartridge fuse, ultra rapid, 110 A, AC 690v, BS88, 20 x 37 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 110Amp 690Vac TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	110Amp 690Vac TYPE T FUSE
Catalog number	110CEET
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-0B14E92086
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 110 A, AC 690v, BS88, 20 x 37 x 139 mm, aR, BS
fuse cartridge, ultra-fast, 110 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS
Fuse, Fuse-link, high speed, 110 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS, offset bolted tags (slotted), dual barrel, 110 mm fixing centres, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-block BH-1132

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Busbar adapter, 3p, for NZM3, 630A, UL508 Type-checked busbar adapter for NZM circuit-breaker and N switch-disconnector, for surface mounting on Cu-busbars 12-30x5-10, double t and triple t profile, rated operational current $I_e=630A$, can be used for NZM3, PN3, N3, adapter width=140mm, rated operating voltage $U_e=690VAC$, screw connection on the busbar 5mm or 10mm thickness, connection top or bottom possible by turning the adapter, temperature resistant to 120 °C, self-extinguishing to UL 94, track resistance CTI 200, number of poles=3 pole, between busbar centers=60mm, can be used in conjunction with busbar system SASY 60i, UL approved, observe derating [Delivery program
Product range 60 mm system Basic function Busbar adapters for NZM Subrange Component adapter for circuit-breakers and switch-disconnectors Function For surface mounting on flat copper busbars 12 - 30 x 5 - 10, double T and triple T profile Rated operational voltage $[U_e]$ 690 V AC Temperature resistant to 120°C Rated diversity factor Ambient temperature $[^{\circ}C]$ 20 30 40 50 60 65 70
Rated operational current, max. $[A]$ 630 605 580 554 529 517 504

Derating with respect to 630 A 1 0,96 0,92 0,88 0,84 0,82 0,80

Self-extinguishing to UL 94 Track resistance CTI 200 Number of poles 3 pole Rated operational current [Ie] 630 A Adapter width 140 mm For use with NZM3,

PN3,

N(S)3 Cu factor 1,47 kg Notes Connection to the system possible at top or bottom via connection on rear

(+)NZM3-XKR13...

Installation is with claw terminal.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 110Amp 690Vac TYPE T FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.