

INDUSTRIAL COMPONENT DATA

125A 240V AC BS88 FUSE 125LET EATON ELECTRIC

Fuse-link, high speed, 12 A, AC 240 V, BS88, 18 x 56 mm, aR, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 125A 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	125A 240V AC BS88 FUSE
Catalog number	125LET
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-87A596415D
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 12 A, AC 240 V, BS88, 18 x 56 mm, aR, BS

125A 240V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, 125A, 280 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC

Fuse, Fuse-link, high speed, 125 A, AC 240 V, DC 150 V, BS88, 18 x 56 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 125LET EAN 5027590429795

UPC 051712830546 Product Length/Depth 55 mm Product Height 18 mm Product Width 18 mm Product Weight 32 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

IEC 60269-4 Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 125 A
Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 280 V
Rated voltage DC 150 V Center-to-center distance of connections 41.5 mm Mounting dimension M6 Current type AC Class
Class aR Clearing (I₂T) 7500 Watt losses 16 W Fuse shape Offset bolted tags Pre arc (I₂T) 600 Color None Interrupt rating
200 kAIC

200 kA RMS Sym, 50 kA DC at 150 Vdc Connection Blade end x blade end Construction size Other Mounting method Stud
Packaging type Standard Voltage rating 280 V Fuse type LET Suitable for TI500 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 125LET Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated volta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 125A 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.