

INDUSTRIAL COMPONENT DATA

12A 690V S/COND FUSE (10) 12ET EATON ELECTRIC cartridge fuse, ultra rapid, 12 A, AC 690 V, DC 500 V, BS88, 1..

Brand: EATON - MOELLER | Manufacturer Part Number: 12A 690V S/COND FUSE (10)



Manufacturer	EATON - MOELLER
MPN / Reference	12A 690V S/COND FUSE (10)
Catalog number	12ET
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-9668A70901
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 12 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS

12A 690V S/COND FUSE (10)

Eaton Busmann series high speed British standard fuse, Single barrel, 12A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

Fuse, Fuse-link, high speed, 12 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed british standard fuse Catalog Number 12ET EAN 5027590432245 UPC 051712830720 Product Length/Depth 82 mm Product Height 39 mm Product Width 91 mm Product Weight 39.4 g

Compliances RoHS Compliant

CE Marked Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 12 A Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V Rated voltage DC 500 V Center-to-center distance of connections 62 mm Mounting dimension M6 Current type AC/DC

Class Class aR Clearing (I2T) 38 at 415 V, 15 at 660 V Watt losses 3.7 W Fuse shape Offset bolted tags Pre arc (I2T) 7
Color None Interrupt rating 200 kA RMS Sym, 50 kA at 500 Vdc Connection Blade end x blade end Construction size Other
Mounting method Stud Voltage rating 690 V (IEC), 700 V (UL) Fuse type ET Suitable for EC-600 Trip indicator kit (indicator
+ clips)
TI700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other
ETIM for 12ET Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
690 V
Rated voltage DC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 12A 690V S/COND FUSE (10) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.