

INDUSTRIAL COMPONENT DATA

12AMP 240V AC BS88 FUSE 12LCT EATON ELECTRIC

Fuse-link, high speed, 12 A, AC 240 V, BS88, 18 x 56 mm, aR, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 12AMP 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	12AMP 240V AC BS88 FUSE
Catalog number	12LCT
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-24E370537C
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 12 A, AC 240 V, BS88, 18 x 56 mm, aR, BS

12AMP 240V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, 12A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, 200 kA RMS Sym.

Fuse, Fuse-link, high speed, 12 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 12LCT EAN 5027590432467 UPC 051712830744 Product Length/Depth 52 mm Product Height 20 mm Product Width 84 mm Product Weight 55 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

UL recognized

IEC 60269-4

CCC Electrical data

Amperage Rating 12 A Voltage rating 240 Vac, 150 Vdc Rated voltage AC 240 V Rated voltage DC 150 V Interrupt rating 200 kA RMS Sym, 50 kA DC at 150 Vdc Class Class aR Pre arc (I2T) 7 Clearing (I2T) 32 Watt losses 2.5 W Product specifications

Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None Compatible Trip indicator/Microswitch

Suitable for TI250 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

ETIM for 12LCT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

240 V

Rated voltage DC (EF012281)

150 V

Rated current (EF000227)

12 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

2.5 W

Mounting holes (EF021553)

M6

Centre-to-centre distance of connectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 12AMP 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.