

INDUSTRIAL COMPONENT DATA

12AMP 690V AC BS88 FUSE 12CT EATON ELECTRIC

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 x 96 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 12AMP 690V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	12AMP 690V AC BS88 FUSE
Catalog number	12CT
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-354266A215
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 x 96 mm, aR, BS

12AMP 690V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, 12 A, 690 V (IEC), 700 V (UL), Non Indicating, 64.2 mm CC, aR (accompanied semiconductor protection)

Fuse, Fuse-link, high speed, 12 A, AC 690 V, DC 500 V, BS88, 9 x 75 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 12CT EAN 5027590432238 UPC 051712830713 Product Length/Depth 82 mm Product Height 21 mm Product Width 90 mm Product Weight 8.35 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

IEC 60269-4 Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 12 A
Breaking capacity 90 kA Fuse indicator Non Indicating Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V
Rated voltage DC 500 V Center-to-center distance of connections 64.2 mm Mounting dimension Other Current type AC/DC
Class Class aR Clearing (I2T) 40 Watt losses 3 W Fuse shape Offset bolted tags Pre arc (I2T) 10 Color None Interrupt
rating 90 kA RMS Sym, 40 kA at 500 Vdc (IEC)
200 kA RMS Sym, 50 kA at 500 Vdc (UL) Connection Blade end x blade end Construction size Other Mounting method
Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type CT Suitable for TI700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other
ETIM for 12CT Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 12AMP 690V AC BS88 FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.