

## INDUSTRIAL COMPONENT DATA

# 12KV 6.3AMP 2.5" HG OIL FUSE 12OHGMA6.3 12OHGMA6-3 EATON ELECTRIC Oil fuse-link, medium voltage, 6.3 A, AC 1..

Brand: EATON - MOELLER | Manufacturer Part Number: 12KV 6.3AMP 2.5" HG OIL FUSE



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | EATON - MOELLER              |
| MPN / Reference | 12KV 6.3AMP 2.5" HG OIL FUSE |
| Catalog number  | 12OHGMA6-3                   |
| Category        | Medium-/high voltage fuse    |
| Minimum order   | 3 Pcs                        |
| Document ID     | EO-519EEEB53                 |
| Generated       | 2026-08-06                   |

## Product Overview

Oil fuse-link, medium voltage, 6.3 A, AC 12 kV, BS2692 F02, 254 x 63.5 mm, back-up, BS, IEC, ESI, with striker

12KV 6.3AMP 2.5" HG OIL FUSE

12KV 6.3AMP 2.5" HG OIL FUSE - Oil fuse-link, medium voltage, 6.3 A, AC 12 kV, 40 kA, BS2692 F02, 254 x 63.5 mm, back-up, BS, IEC, ESI, with striker, oil-tight

Fuse, Oil fuse-link, medium voltage, 6.3 A, AC 12 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker, cylindrical, oil-tight, protection of primary side transformer, and oil-filled fuse switch combination unit, BS2692-1, IEC 60282-1, ESI 12-8, Breaking Capacity 40 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Busmann Series Medium Voltage fuses and accessories

## Additional Product Information

Oil fuse-link, medium voltage, 6.3 A, AC 12 kV, 40 kA, BS2692 F02, 254 x 63.5 mm, back-up, BS, IEC, ESI, with striker, oil-tight  
Fuse, Oil fuse-link, medium voltage, 6.3 A, AC 12 kV, BS2692 F02, 254 x 63.5 mm, back-up, BS, IEC, ESI, with striker, cylindrical, oil-tight, protection of primary side transformer, and oil-filled fuse switch combination unit, BS2692-1, IEC 60282-1, ESI 12-8, Breaking Capacity 40 kA  
Delivery program

Product rangeFuseBasic functionOil fuse-linkField of applicationmedium voltageRated current [I]<sub>N</sub>6.3 ARated voltageAC 12 kVConstruction sizeBS2692 F02Size254 x 63.5 mmUtilization categoryback-upStatus indicatorwith strikerDescriptionoil-tightBreaking Capacity40 kAusable for size/applicationsprotection of primary side transformer, and oil-filled fuse switch combination unitStandard/ApprovalBS IEC

ESIShapecylindricalStandards/RegulationsBS2692-1

IEC 60282-1

ESI 12-8Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)Rated current6.3 ARated voltage12 kVVoltage typeACRated frequency50 - 50 HzBreaking capacity40 kAUtilization categoryOtherApplicationPrimary side transformer protectionLength254 mmDiameter63.5 mmPerformance category according to IEC 60282-1Back-upWith strikerYesStandardBritish StandardRelease characteristicOtherInstallation techniqueOil

ETIM for 12OHGMA6.3 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

6.3 A

Rated voltage (EF000228)

12 kV

Voltage type (EF000...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 12KV 6.3AMP 2.5" HG OIL FUSE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.