

INDUSTRIAL COMPONENT DATA

140A TYPE T FUSE (5) 140CEET 140CEET EATON ELECTRIC cartridge fuse, ultra rapid, 140 A, AC 690v, BS88, 20 x ..

Brand: EATON - MOELLER | Manufacturer Part Number: 140A TYPE T FUSE (5) 140CEET



Manufacturer	EATON - MOELLER
MPN / Reference	140A TYPE T FUSE (5) 140CEET
Catalog number	140CEET
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-8E20B184CB
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 140 A, AC 690v, BS88, 20 x 37 x 139 mm, aR, BS
fuse cartridge, ultra fast, 140 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS
140A 690V AC TYPE T FUSE (5) - Fuse-link, high speed, 140 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS
Fuse, Fuse-link, high speed, 140 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS, offset bolted tags (slotted), dual barrel, 110 mm fixing centres, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-block BH-1132

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 140 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS Fuse, Fuse-link, high speed, 140 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS, offset bolted tags (slotted), dual barrel, 110 mm fixing centres, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-block BH-1132 Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 140 A Rated voltage AC 690 V Construction size BS88 Size 20 x 37 x 139 mm Utilization category aR Description 110 mm fixing centres Breaking Capacity 200 kA usable for size/applications protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters Standard/Approval BS Shape offset bolted tags (slotted), dual barrel Standards/Regulations BS88-4 IEC 60269-4 Optional accessories fuse-block BH-1132 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 140 A Rated voltage 690 V Voltage type AC Rated switching capacity 200 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No
ETIM for 140CEET Circuit breakers an...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 140A TYPE T FUSE (5) 140CEET with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.