

INDUSTRIAL COMPONENT DATA

140A 690V AC TYPE T FUSE (5) 140EET EATON ELECTRIC cartridge fuse, ultra rapid, 140 A, AC 690 V, DC 500 V, B..

Brand: EATON - MOELLER | Manufacturer Part Number: 140A 690V AC TYPE T FUSE (5)



Manufacturer	EATON - MOELLER
MPN / Reference	140A 690V AC TYPE T FUSE (5)
Catalog number	140EET
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-EBC4194E4E
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 140 A, AC 690 V, DC 500 V, BS88, 37 x 94 mm, aR, BS

140A 690V AC TYPE T FUSE (5)

Eaton Busmann series high speed British standard fuse, Double barrel, 140A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

Fuse, Fuse-link, high speed, 140 A, AC 690 V, DC 500 V, BS88, 37 x 94 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-1132

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed british standard fuse Catalog Number 140EET EAN 5027590433556
UPC 051712830935 Product Length/Depth 94 mm Product Height 36 mm Product Width 20 mm Product Weight 91.6 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

IEC 60269-4 Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 140 A

Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V Rated voltage DC 500 V Center-to-center distance of connections 71 mm Mounting dimension M8 Current type AC/DC Class Class aR Clearing (I2T) 7000 at 415 V, 12000 at 660 V Watt losses 35 W Fuse shape Offset bolted tags Pre arc (I2T) 1050 Color None Interrupt rating 200 kA RMS Sym, 50 kA at 500 Vdc Connection Blade end x blade end Construction size Other Mounting method Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type EET Suitable for EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 140EET Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 140A 690V AC TYPE T FUSE (5) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.