

INDUSTRIAL COMPONENT DATA

1500AMP 250V AC SEMI-COND FWX-1500AH EATON ELECTRIC Microswitch, high speed, 5 A, AC 250 V, type T indicator..

Brand: EATON - MOELLER | Manufacturer Part Number: 1500AMP 250V AC SEMI-COND



Manufacturer	EATON - MOELLER
MPN / Reference	1500AMP 250V AC SEMI-COND
Catalog number	FWX-1500AH
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-AC41C83312
Generated	2026-08-06

Product Overview

Microswitch, high speed, 5 A, AC 250 V, type T indicator, 6.3 x 0.8 lug dimensions, 000 to 3 with straight tags, 1mA-5A, 4V-250V

1500AMP 250V AC SEMI-COND

Fuse-link, high speed, 1500 A, AC 250 V, 200 kA, 48 x 89 mm, aR, UL

Fuse, Fuse-link, high speed, 1500 A, AC 250 V, 48 x 89 mm, UL, cylindrical with flush end contacts, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 1500 A, AC 250 V, 200 kA, 48 x 89 mm, aR, UL
Fuse, Fuse-link, high speed, 1500 A, AC 250 V, 48 x 89 mm, UL, cylindrical with flush end contacts, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL, Breaking Capacity 200 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 1500 A
Rated voltage AC 250 V
Size 48 x 89 mm
Utilization category aR
Breaking Capacity 200 kA
Usable for size/applications DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval UL
Shape cylindrical with flush end contacts
Standards/Regulations UL
Technical data ETIM 7.0

Aparatos de protección y fusibles (EG000020) / Fusible para baja tensión tipo NH (EC000055) Tecnología electrónica, de

automatización y de mando de procesos / Instalación eléctricas, equipo / Inserto de fusibles / Inserto de fusibles de baja tensión ( [AFZ800015])Tamaño de construcciónOtrosCorriente nominal1500 AmpereTensión nominal250 VoltTipo de tensiónCACapacidad de conmutación nominal/poder de corte200 kiloampereCategoría de usoOtrosTipo de indicador de estado de fusibleNinguno

ETIM for FWX-1500AH Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type B

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

250 V

Rated curren...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 1500AMP 250V AC SEMI-COND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.