

INDUSTRIAL COMPONENT DATA

SEMI-COND FUSE 225A 150V AC FWA-225B EATON

ELECTRIC cartridge fuse, ultra rapid, 225 A, AC 150 V, DC 150 V, ..

Brand: EATON - MOELLER | Manufacturer Part Number: SEMI-COND FUSE 225A 150V AC



Manufacturer	EATON - MOELLER
MPN / Reference	SEMI-COND FUSE 225A 150V AC
Catalog number	FWA-225B
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-45B30F7C55
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 225 A, AC 150 V, DC 150 V, 25 x 68 mm, UL

SEMI-COND FUSE 225A 150V AC

Eaton Bussmann series FWA high speed fuse, 500 Vac (0.25-6.3A), 500 Vdc (2-5A), 225A, None, High speed fuse

Fuse, Fuse-link, high speed, 225 A, AC 150 V, DC 150 V, 25 x 68 mm, UL, cylindrical with centre-bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248, Breaking Capacity 100 kA, Optional accessories BH series fuse blocks

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWA-225B EAN 5027590088695 UPC 051712577984 Product Length/Depth 25.4 mm Product Height 25.4 mm Product Width 67 mm Product Weight 83 g

Compliances Contact factory

Contact Manufacturer Electrical data

Amperage Rating 225 A Voltage rating 150 Vac/dc Voltage type AC/DC Interrupt rating 100 kAIC at 150 Vac

100 kAIC at 80 Vdc

20 kAIC at 150 Vdc Class Class aR Pre arc (I2T) 4780 Clearing (I2T) 45000 Watt losses 17.6 W Product specification

Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Fuse indicator Non Indicating
ETIM for FWA-225B Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

150 V

Rated voltage DC (EF012281)

150 V

Rated current (EF000227)

225 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

17.6 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

50 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SEMI-COND FUSE 225A 150V AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.