

INDUSTRIAL COMPONENT DATA

15KV 20A EXPULSION LINK 15TU20 EATON ELECTRIC Air fuse-link, medium voltage, 20 A, AC 36 kV, 50.8 x 565mm, b..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 20A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 20A EXPULSION LINK
Catalog number	15TU20
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-FB1F59C754
Generated	2026-08-06

Product Overview

Air fuse-link, medium voltage, 20 A, AC 36 kV, 50.8 x 565mm, back-up, BS, with striker, style 36 tags

15KV 20A EXPULSION LINK

Expulsion fuse-link, medium voltage, 20 A, AC 15 kV, 533 mm, ANSI, T slow, style U termination

Fuse, Expulsion fuse-link, medium voltage, 20 A, AC 15 kV, 533 mm, ANSI, T slow, universal with slip off NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 15TU20 EAN 5027590436380

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 44.44 g Certifications

ANSI/IEEE Std C37.42 Product specifications

Type Medium Voltage Expulsion Fuse Link Application Primary side transformer protection, feeder protection, capacitor bank protection Amperage Rating 20 A Current characteristic type Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics Rated frequency - max 60 Hz Rated frequency - min 50 Hz Release characteristic T Standard ANSI Type of termination Universal Voltage type AC Color Green Interrupt rating 8 kAIC Construction size 533 mm Voltage rating 15 kV

ETIM for 15TU20 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

20 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

T

Type of termination (EF012540)

Universal

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 20A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.