

INDUSTRIAL COMPONENT DATA

15KV 2A LK 15XAB2 EATON ELECTRIC Cartridge fuse, expulsion, MT, 2 A, AC 15 kV, 533 mm, ANSI, XA extra rapid

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 2A LK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 2A LK
Catalog number	15XAB2
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-613DAE5713
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 2 A, AC 15 kV, 533 mm, ANSI, XA extra rapid

Ejection Fuse Cartridge, MT, 2 A, AC 15 kV, 533 mm, ANSI, XA extra rapid

15XAB2 - Expulsion fuse-link, medium voltage, 2 A, AC 15 kV, 533 mm, ANSI, XA extra rapid

Fuse, Expulsion fuse-link, medium voltage, 2 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann fuses
--------------	---------------------------------

Additional Product Information

Expulsion fuse-link, medium voltage, 2 A, AC 15 kV, 533 mm, ANSI, XA extra rapid Fuse, Expulsion fuse-link, medium voltage, 2 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program

Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 2 A Rated voltage AC 15 kV Size 533 mm Description fixed NEMA button head link Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] XA extra rapid Standard/Approval ANSI Standards/Regulations ANSI C37-42

ETIM for 15XAB2 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

2 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 2A LK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.