

## INDUSTRIAL COMPONENT DATA

# 15KV 3 AMP EXPULSION LINK 15KU3 EATON ELECTRIC

## Expulsion fuse-link, medium voltage, 3 A, AC 15 kV, 533 mm, A..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 3 AMP EXPULSION LINK



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | 15KV 3 AMP EXPULSION LINK           |
| Catalog number  | 15KU3                               |
| Category        | Expulsion fuse-link, medium voltage |
| Minimum order   | 25 Pcs                              |
| Document ID     | EO-AB757D2811                       |
| Generated       | 2026-08-06                          |

### Product Overview

Expulsion fuse-link, medium voltage, 3 A, AC 15 kV, 533 mm, ANSI, K fast, style U termination

15KV 3 AMP EXPULSION LINK

Fuse, Expulsion fuse-link, medium voltage, 3 A, AC 15 kV, 533 mm, ANSI, K fast, universal with slip off NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

### Additional Product Information

#### General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 15KU3 EAN 5027590435710

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 19.24 g Certifications

ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 3 A Voltage rating 15 kV Voltage type AC Current characteristic type Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics Rated frequency - min 50 Hz Product specification

Construction size 533 mm Standard ANSI Type of termination Universal Color Yellow

ETIM for 15KU3 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

3 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

K

Type of termination (EF012540)

Universal

Standard (EF009322)

ANSI

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 3 AMP EXPULSION LINK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.