

INDUSTRIAL COMPONENT DATA

15KV 30AMP LINK 15KD30 15KD30 EATON ELECTRIC

Expulsion fuse-link, medium voltage, 30 A, AC 15 kV, 533 mm, AN..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 30AMP LINK 15KD30



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 30AMP LINK 15KD30
Catalog number	15KD30
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-80C4C810DB
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 30 A, AC 15 kV, 533 mm, ANSI, K fast, style D termination

Ejection fuse cartridge, MT, 30 A, AC 15 kV, 533 mm, ANSI, K fast

Fuse, Expulsion fuse-link, medium voltage, 30 A, AC 15 kV, 533 mm, ANSI, K fast, Double tailed link without NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories
--------------	---

Additional Product Information

Expulsion fuse-link, medium voltage, 30 A, AC 15 kV, 533 mm, ANSI, K fast, style D termination Fuse, Expulsion fuse-link, medium voltage, 30 A, AC 15 kV, 533 mm, ANSI, K fast, Double tailed link without NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 30 A Rated voltage AC 15 kV Size 533 mm Description Double tailed link without NEMA button head Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] K fast Standard/Approval ANSI Standards/Regulations ANSI C37-42 ETIM for 15KD30 Circuit breakers and fuses (EC003611) Feature Name Feature Value

Rated current (EF000227)

30 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

K

Type of termination (EF012540)

Double tail

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 30AMP LINK 15KD30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.