

INDUSTRIAL COMPONENT DATA

15KV 40AMP EXPULSION LINK 15TD40 EATON ELECTRIC

Expulsion fuse-link, medium voltage, 40 A, AC 15 kV, 533 mm,..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 40AMP EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 40AMP EXPULSION LINK
Catalog number	15TD40
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-16EC75D3FF
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 40 A, AC 15 kV, 533 mm, ANSI, T slow, style D termination

15KV 40AMP EXPULSION LINK

Fuse, Expulsion fuse-link, medium voltage, 40 A, AC 15 kV, 533 mm, ANSI, T slow, Double tailed link without NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 15TD40 EAN 5027590436267

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 46.84 g Certifications

ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 40 A Voltage rating 15 kV Voltage type AC Current characteristic type Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics Rated frequency - min 50 Hz Product specification

Construction size 533 mm Standard ANSI Type of termination Double tail Color Green

ETIM for 15TD40 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

40 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

T

Type of termination (EF012540)

Double tail

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 40AMP EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.