

INDUSTRIAL COMPONENT DATA

15KV 50AMP EXPULSION LINK 15XABR50 EATON ELECTRIC

Cartridge fuse, expulsion, MT, 50 A, AC 15 kV, 533 mm, ANSI..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 50AMP EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 50AMP EXPULSION LINK
Catalog number	15XABR50
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-3046E09D73
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 50 A, AC 15 kV, 533 mm, ANSI, XA extra rapid

15KV 50AMP EXPULSION LINK

Expulsion fuse-link, medium voltage, 50 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, style BR termination

Fuse, Expulsion fuse-link, medium voltage, 50 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link with 1/4 inch UNF thread, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 15XABR50 EAN 5027590436830
UPC 051712520744 Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 44.76 g
Certifications ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 50 A Voltage rating 15 kV Voltage type AC Current characteristic type Type XA - This type of expulsion fuse link has an extra rapid characteristic. It is suitable for applications where a high degree of system protection is required at the expense of discrimination. Rated frequency - min 50 Hz Product specification

Construction size 533 mm Standard ANSI Type of termination Removable buttonhead Color Pink

ETIM for 15XABR50 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

50 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Removable buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 50AMP EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.