

INDUSTRIAL COMPONENT DATA

15KV 65AMP LINK 15XAB65 XTPEXT065DD EATON ELECTRIC Cartridge fuse, expulsion, MT, 65 A, AC 15 kV, 533 mm, AN..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 65AMP LINK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 65AMP LINK
Catalog number	XTPEXT065DD
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-F662571D42
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 65 A, AC 15 kV, 533 mm, ANSI, XA extra rapid
Ejection Fuse Cartridge, MT, 65 A, AC 15 kV, 533 mm, ANSI, XA extra rapid
15XAB65 - Expulsion fuse-link, medium voltage, 65 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, style B termination
Fuse, Expulsion fuse-link, medium voltage, 65 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann fuses
--------------	---------------------------------

Additional Product Information

Expulsion fuse-link, medium voltage, 65 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, style B termination Fuse, Expulsion fuse-link, medium voltage, 65 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program
Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 65 A Rated voltage AC 15 kV Size 533 mm Description fixed NEMA button head link Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] XA extra rapid
Standard/Approval ANSI Standards/Regulations ANSI C37-42
ETIM for 15XAB65 Circuit breakers and fuses (EC003611)
Feature Name
Feature Value
Rated current (EF000227)

65 A
Rated voltage (EF000228)
15 kV
Voltage type (EF000187)
AC
Rated frequency (EF001663)
50 Hz
Release characteristic (EF000889)
Other
Type of termination (EF012540)
Fixed buttonhead
Standard (EF009322)
ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 65AMP LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.