

INDUSTRIAL COMPONENT DATA

15KV 65AMP EXPULSION LINK 15XABR65 EATON ELECTRIC

Cartridge fuse, expulsion, MT, 65 A, AC 15 kV, 533 mm, ANSI..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 65AMP EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 65AMP EXPULSION LINK
Catalog number	15XABR65
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-E8D5DAF3D8
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 65 A, AC 15 kV, 533 mm, ANSI, XA extra rapid

15KV 65AMP EXPULSION LINK

15KV 65AMP EXPULSION LINK - Expulsion fuse-link, medium voltage, 65 A, AC 15 kV, 8 kA, 533 mm, ANSI, removable NEMA button head link, XA extra rapid

Fuse, Expulsion fuse-link, medium voltage, 65 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link with 1/4 inch UNF thread, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 15XABR65 EAN 5027590436854

UPC 051712491556 Product Length/Depth 102 mm Product Height 233 mm Product Width 77 mm Product Weight 26.2 g

Certifications ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 65 A Voltage rating 15 kV Voltage type AC Current characteristic type Type XA - This type of expulsion fuse link has an extra rapid characteristic. It is suitable for applications where a high degree of system protection is required at the expense of discrimination. Rated frequency - min 50 Hz Product specification

Construction size 533 mm Standard ANSI Type of termination Removable buttonhead Color Pink

ETIM for 15XABR65 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

65 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Removable buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 65AMP EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.